

# Series 2112

## Quick Lock Rubber Push-On Hose



This oil resistant hose is excellent for use with air tools, to convey water, mild chemicals, and various petroleum products. No clamps or special tools needed. Special braid angle for quick and secure push-on coupling retention. Not recommended for gasoline or diesel fuels. Available in various colors for color-coding. Black cover meets MSHA 30 CFR 18.65 (Flame Resistant).

Tube:	Black Nitrile (ARPM Class A ORS)
Reinforcement:	Braided, high tensile textile
Cover:	Nitrile/PVC – (ARPM Class B ORS)
Temperature:	-40° F.to +212°F. (-40°C.to +100°C.)
Branding:	Ink brand – white or black letters

Part #	Inside Diameter		Outside Diameter		Working Pressure (PSI)	Burst (PSI)	Weight Lbs/Ft	Coupling Series
	(In.)	(MM)	(In.)	(MM)				
2112-025	1/4	6.4	0.47	11.9	300	1200	0.09	PL
2112-038	3/8	9.5	0.63	16.0	300	1200	0.11	PL
2112-050	1/2	12.7	0.77	19.6	300	1200	0.15	PL
2112-063	5/8	15.9	0.94	23.8	300	1200	0.20	PL
2112-075	3/4	19.1	1.06	26.9	300	1200	0.24	PL