Series 2115 Quick Lock Push-On Hose



This oil resistant hose is excellent for use with air tools, to convey water, mild chemicals, and various petroleum products. No clamps or special tools needed. Special braid angle for quick and secure push-on coupling retention. Not recommended for gasoline or diesel fuels. Available in various colors for colorcoding. Black cover meets MSHA 30 CFR 18.65 (Flame Resistant).

Tube: Black Nitrile (ARPM Class A ORS)

Reinforcement: Braided, high tensile textile

Cover: Nitrile/PVC - (ARPM Class B ORS)

Black, Blue, Gray, Green, Red, or Yellow

Temperature: $-40^{\circ}\text{F to } +212^{\circ}\text{F } (-40^{\circ}\text{C to } +100^{\circ}\text{C})$

Design Factor: 4:1

Branding: Ink Brand – White or Black Letters

Origin: USA

Part #	I.D. (In)	O.D.	W.P. (PSI)	Weight (Lbs / Ft)	Std. Length	Stock (Yes) or Min. Order
2115BK-025	1/4	.47	300	.09	300′	Yes
2115BK-038	3/8	.63	300	.11	300′	Yes
2115BK-050	1/2	.77	300	.15	300′	Yes
2115BK-063	5/8	.94	300	.20	250′	Yes
2115BK-075	3/4	1.06	300	.24	225′	Yes

- Black Cover "BK"
- Gray Cover "GY"
- Green Cover "GN"

- Red Cover "RD"
- Blue Cover "BL"
- Yellow Cover "YL"