

## Series 2318 Plaster & Concrete Hose (Textile Reinforced)



Designed for use in the pumping of plaster, grout, and shotcrete. Specially compounded tube is highly resistant to abrasive materials. The heavy wall resists kinking and the tube/cover is static dissipating. For use as a flexible connection between pumping equipment and hard piping. **Meets or exceeds CPMA 27-200.**

<b>Tube:</b>	Natural rubber blend. Static conducting
<b>Reinforcement:</b>	Multiple textile plies
<b>Cover:</b>	Black SBR
<b>Temperature:</b>	-25°F to +180°F
<b>Branding:</b>	White Mylar / Black Letters

Part #	I.D. (In)	O.D. (In)	W.P. (PSI)	Weight Per 100 Ft (Lbs)	Std. Length	Stock (Yes) or Min. Order
2318-125	1-1/4	1.93	1233.0	80.0	50'	400'
2318-150	1-1/2	2.31	1233.0	114.0	50'	400'
2318-200	2	2.83	1233.0	146.0	50'	Yes
2318-250	2-1/2	3.40	1233.0	196.0	50'	Yes
2318-300	3	3.92	1233.0	239.0	50'	Yes
2318-400	4	4.94	1233.0	310.0	50'	400'
2318-500	5	5.94	1233.0	376.0	50'	400'