



ASSEMBLY MATERIALS:

FLANGES: CARBON STEEL CLASS 150

HOSE/BRAID: STAINLESS STEEL 300 SERIES

90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	1.50"	420-150-2	+/- 2"	27.875"	12.25"	472	
	2.00"	420-200-2	+/- 2"	31.875"	14"	516	
	2.50"	420-250-2	+/- 2"	37.75"	16.5"	387	
	3.00"	420-300-2	+/- 2"	40.375"	17.5"	316	
	4.00"	420-400-2	+/- 2"	47"	20.25"	232	
	5.00"	420-500-2	+/- 2"	55"	23.5"	191	
	6.00"	420-600-2	+/- 2"	60.5"	25.50"	165	
	8.00"	420-800-2	+/- 2"	72.5"	29.75"	234	
	10.00"	420-1000-2	+/- 2"	85.375"	34.75"	230	
	12.00"	420-1200-2	+/- 2"	96"	38.5"	161	
	14.00"	420-1400-2	+/- 2"	108.5"	42.75"	150	

NOTES: CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

0	RELEASED	06/15	KJ
REV	DESCRIPTION	DATE	APPROVED

REVISION HISTORY



8040 N.E. 33rd Dr
Portland, OR 97211
Ph: 503.281.4673, Fax 503.281.5845

UNISOURCE V-LOOP

FLANGED ENDS - +/- 2" MOVEMENT

DRAWN BY:	BC	DATE:	06/15/15
DWG NO:	420-2.idw	SCALE:	NONE

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____