

ASSEMBLY MATERIALS:

FLANGES: CARBON STEEL CLASS 150

HOSE/BRAID: STAINLESS STEEL 300 SERIES

90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40


QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	1.50"	420-150-4	+/- 4"	35.625"	16.25"	472	
	2.00"	420-200-4	+/- 4"	40.375"	18.25"	516	
	2.50"	420-250-4	+/- 4"	47.625"	21.5"	387	
	3.00"	420-300-4	+/- 4"	51"	22.875"	316	
	4.00"	420-400-4	+/- 4"	58.375"	26"	232	
	5.00"	420-500-4	+/- 4"	67.875"	29.875"	191	
	6.00"	420-600-4	+/- 4"	74.25"	32.25"	165	
	8.00"	420-800-4	+/- 4"	86.75"	36.875"	234	
	10.00"	420-1000-4	+/- 4"	101.625"	42.875"	230	
	12.00"	420-1200-4	+/- 4"	113.625"	47.375"	161	
	14.00"	420-1400-4	+/- 4"	126.875"	51.875"	150	

NOTES: CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

0	RELEASED	06/15	KJ
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE V-LOOP FLANGED ENDS - +/- 4" MOVEMENT			
DRAWN BY:	BC	DATE:	06/15/15
DWG NO:	420-4.idw	SCALE:	NONE