

# Series 3013

## SAE 100R13



Extreme high pressure hose suitable for use with petroleum based hydraulic fluids, lubricating oils, water, and water emulsion hydraulic fluids. MSHA approved cover. Fabric impression.

- Tube:** Type A maximum oil resistant synthetic rubber.
- Reinforcement:** 4 to 6 spirals of high tensile steel wire.
- Cover:** Abrasion, oil, chemical, and weather resistant wrapped cover. MSHA approved.
- Temperature:** -40° F. to +250° F. (-40° C. to +120° C.)
- Branding:** Clear Mylar / White letters with orange box.

Part #	Inside Diameter		Outside Diameter		W.P. (PSI)	Burst (PSI)	Minimum Bend Rad (In.)	Weight Lbs/Ft	Coupling Series
	(In.)	(MM)	(In.)	(MM)					
3013-12	3/4	19.1	1.3	32.0	5000	20,000	9.4	1.1	HW
3013-16	1	25.4	1.5	38.4	5000	20,000	11.8	1.4	HW
3013-20	1-1/4	31.8	1.9	49.3	5000	20,000	16.5	2.7	HW
3013-24	1-1/2	38.1	2.3	57.3	5000	20,000	19.7	3.4	HW
3013-32	2	50.8	2.8	71.6	5000	20,000	24.8	4.4	HW