

**ASSEMBLY MATERIALS:**

**THREADED FITTINGS:** CARBON STEEL SCH 40

**HOSE/BRAID:** STAINLESS STEEL 300 SERIES


**90° ELBOWS:** CARBON STEEL SCH 40 LR

**45° ELBOWS:** CARBON STEEL SCH 40

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	.50"	425-050-2	+/- 2"	21.875"	8.5"	1075	
	.75"	425-075-2	+/- 2"	22.375"	9.375"	792	
	1.00"	425-100-2	+/- 2"	26.75"	10.5"	571	
	1.25"	425-125-2	+/- 2"	29.25"	11.625"	531	
	1.50"	425-150-2	+/- 2"	30.875"	12.25"	472	
	2.00"	425-200-2	+/- 2"	34.875"	14"	516	
	2.50"	425-250-2	+/- 2"	41.75"	16.5"	387	
	3.00"	425-300-2	+/- 2"	45.375"	17.5"	316	
	4.00"	425-400-2	+/- 2"	54"	20.25"	232	

NOTES: CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GOT TO [WWW.UNISOURCE-MFG.COM](http://WWW.UNISOURCE-MFG.COM) FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: \_\_\_\_\_  
 PROJECT: \_\_\_\_\_  
 ENGINEER: \_\_\_\_\_

0	RELEASED	06/15	BC
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
<b>UNISOURCE V-LOOP</b> THREADED ENDS - +/- 2" MOVEMENT			
DRAWN BY:	BC	DATE:	06/15/15
DWG NO:	425-2.idw	SCALE:	NONE