

ASSEMBLY MATERIALS:

GROOVED FITTINGS: CARBON STEEL SCH 40

HOSE/BRAID: STAINLESS STEEL 300 SERIES

90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40




FOR FIRE PROTECTION SYSTEMS

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	1.50"	436-150-8	+/- 8"	52"	21.875"	300	
	2.00"	436-200-8	+/- 8"	57.375"	24.25"	300	
	2.50"	436-250-8	+/- 8"	66.75"	28.5"	300	
	3.00"	436-300-8	+/- 8"	71.5"	30.625"	300	
	4.00"	436-400-8	+/- 8"	80.25"	34.5"	175	
	5.00"	436-500-8	+/- 8"	90.25"	38.625"	175	
	6.00"	436-600-8	+/- 8"	98"	41.875"	175	
	8.00"	436-800-8	+/- 8"	112"	46.375	175	

NOTES: ASSEMBLIES COMPATIBLE WITH WET AND DRY FIRE PROTECTION SYSTEMS. CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: _____
 PROJECT: _____
 ENGINEER: _____

0	RELEASED	06/15	KJ
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE FIRE V GROOVED ENDS - +/- 8" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 436-8.idw		SCALE: NONE	