



ASSEMBLY MATERIALS:

THREADED FITTINGS: CARBON STEEL SCH 40

HOSE/BRAID: STAINLESS STEEL 300 SERIES

90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40



QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	BEND RAD	PSI	COMMENTS
	.50"	445-050-4	+/- 4"	31.75"	13.5"	6"	150	
	.75"	445-075-4	+/- 4"	32.25"	14.25"	8"	150	
	1.00"	445-100-4	+/- 4"	36.75"	15.5"	9"	150	
	1.25"	445-125-4	+/- 4"	44.75"	19.5"	10.5"	150	
	1.50"	445-150-4	+/- 4"	47.125"	20.5"	12"	150	
	2.00"	445-200-4	+/- 4"	50.50"	21.75"	15"	150	
	2.50"	445-250-4	+/- 4"	60.125"	25.75"	20"	150	
	3.00"	445-300-4	+/- 4"	64.5"	27.125"	22"	150	
	4.00"	445-400-4	+/- 4"	71"	29.5"	27"	150	

NOTES: CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GOT TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

ASSEMBLY MEETS THE REQUIREMENTS SET FORTH BY ANSI/UL 536 STANDARD FOR FLEXIBLE METAL HOSE.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

0	RELEASED	06/15	BC
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE V-LOOP CSA THREADED ENDS - +/- 4" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 445-4.idw		SCALE: NONE	