



ASSEMBLY MATERIALS:

HOSE/BRAID: STAINLESS STEEL 300 SERIES

90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40



QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	.50"	450-050-4	+/- 4"	28.75"	13.5"	150	
	.75"	450-075-4	+/- 4"	29.25"	14.25"	150	
	1.00"	450-100-4	+/- 4"	32.75"	15.5"	150	
	1.25"	450-125-4	+/- 4"	40.75"	19.5"	150	
	1.50"	450-150-4	+/- 4"	43.125"	20.5"	150	
	2.00"	450-200-4	+/- 4"	46.5"	21.75"	150	
	2.50"	450-250-4	+/- 4"	60.125"	25.75"	150	
	3.00"	450-300-4	+/- 4"	58.5"	27.125"	150	
	4.00"	450-400-4	+/- 4"	64.375"	29.5"	150	

NOTES: CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GOT TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

ASSEMBLY MEETS THE REQUIREMENTS SET FORTH BY ANSI/UL 536 STANDARD FOR FLEXIBLE METAL HOSE.

CUSTOMER: _____
 PROJECT: _____
 ENGINEER: _____

0	RELEASED	06/15	BC
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
UNISOURCE^{mfg.}			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE V-LOOP CSA WELD ENDS - +/- 4" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 450-4.idw		SCALE: NONE	