



ASSEMBLY MATERIALS:

THREADED FITTINGS: CARBON STEEL SCH 40

HOSE/BRAID: STAINLESS STEEL 300 SERIES

90° ELBOWS: CARBON STEEL SCH 40 LR

45° ELBOWS: CARBON STEEL SCH 40



FOR FIRE PROTECTION SYSTEMS

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	.50"	426-050-8	+/- 8"	37.375"	16.375"	300	
	.75"	426-075-8	+/- 8"	39.375"	17.75"	300	
	1.00"	426-100-8	+/- 8"	44.5"	19.375"	300	
	1.25"	426-125-8	+/- 8"	47.5"	20.875"	300	
	1.50"	426-150-8	+/- 8"	50"	21.875"	300	
	2.00"	426-200-8	+/- 8"	55.375"	24.25"	300	
	2.50"	426-250-8	+/- 8"	65.75"	28.5"	300	
	3.00"	426-300-8	+/- 8"	71.5"	30.625"	300	
	4.00"	426-400-8	+/- 8"	82.25"	34.5"	175	

NOTES: ASSEMBLIES COMPATIBLE WITH WET AND DRY FIRE PROTECTION SYSTEMS. CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GO TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: _____
 PROJECT: _____
 ENGINEER: _____

0	RELEASED	06/15	BC
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
UNISOURCE FIRE V THREADED ENDS - +/- 8" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 426-8.idw		SCALE: NONE	