

FOR FIRE PROTECTION SYSTEMS


**ASSEMBLY MATERIALS:**

- GROOVED FITTINGS:** CARBON STEEL SCH 40
- HOSE/BRAID:** STAINLESS STEEL 300 SERIES
- 90° ELBOWS:** CARBON STEEL SCH 40 LR

QTY	SIZE	MODEL	MOVEMENT	OAL	HEIGHT	PSI	COMMENTS
	1.50"	436U-150-4	+/- 4"	17"	19.5"	300	
	2.00"	436U-200-4	+/- 4"	18.875"	22.75"	300	
	2.50"	436U-250-4	+/- 4"	21"	27"	300	
	3.00"	436U-300-4	+/- 4"	24"	29.25"	300	
	4.00"	436U-400-4	+/- 4"	30"	34.75"	175	
	5.00"	436U-500-4	+/- 4"	36"	40.875"	175	
	6.00"	436U-600-4	+/- 4"	42"	45.375"	175	
	8.00"	436U-800-4	+/- 4"	56"	54.375"	175	

NOTES: ASSEMBLIES COMPATIBLE WITH WET AND DRY FIRE PROTECTION SYSTEMS. CONTACT FACTORY FOR MOVEMENTS AND SIZES NOT SHOWN. GOT TO WWW.UNISOURCE-MFG.COM FOR INSTALLATION INSTRUCTIONS. PRESSURES LISTED ARE AT 70°F. MAX WORKING TEMPERATURE 800°F.

CUSTOMER: \_\_\_\_\_  
 PROJECT: \_\_\_\_\_  
 ENGINEER: \_\_\_\_\_

0	RELEASED	06/15	KJ
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			
			
8040 N.E. 33rd Dr Portland, OR 97211 Ph: 503.281.4673, Fax 503.281.5845			
<b>UNISOURCE FIRE U</b> GROOVED ENDS - +/- 4" MOVEMENT			
DRAWN BY: BC		DATE: 06/15/15	
DWG NO: 436-4.idw		SCALE: NONE	