

TECHNICAL DATA SHEET

# CUP-CEP

MULTI-STAGE BOWL TYPE DIFFUSER PUMP

## **PUMP OVERVIEW**

The ClydeUnion Pumps Condensate Extraction Pump (CUP-CEP) is a vertically suspended, mixed flow, bowl pump range designed specifically for the requirements of the power generation industry.

The pumps can be configured with either above or below floor suction to suit specific plant design considerations. Additionally, the full range of pumps can be provided with either a single or double suction inlet stage to closely match your site NPSH, thereby optimizing the solution provided.



#### **TYPICAL APPLICATIONS**

- Condensate extraction
- Heater drains

### **TECHNICAL DATA**

Capacity:	up to 13,200 USgpm / 3,000 m³/hr
Delivery head:	up to 1,480 ft / 450 m
Temperature:	up to 185 °F / 85 °C
Speeds:	up to 1,800 rpm



#### **FEATURES + BENEFITS**

#### 1 Canister + seal venting

Common seal and canister vent connection. Simplified pipe arrangement

#### (2) Lineshaft coupling

Flangeless coupling secured over the shaft ends and located via keys over the shaft

# $(\mathbf{3})$ Standard wear ring fitment to pump end

Optimum efficiency can be maintained by replacing bowl wear ring if required

## 4 Hydraulic design

Flexible impeller and bowl combinations for optimized range coverage and efficient hydraulic performance

#### **(5)** Optimized suction performance

Available as single entry or double entry depending on NPSH

#### 6 Centralizing webs

Standard across full range. Guides pump into the central position providing ease of assembly

#### **(7)** Suction nozzle

Above or below floor suction options. Located in headpiece or canister


#### (8) Sleeved impeller retention

Impellers are retained by sleeves and positively secured by a locking nut mechanism. Impellers can be removed more easily at overhaul




#### **RANGE COVERAGE CHARTS**

#### 60HZ RANGE CHART



#### **50HZ RANGE CHART**



#### These charts cover the standard pump range. Other engineering designs exist for extreme applications



P: +44 (0)141 637 7141 F: +44 (0)141 633 2399 E: cu.sales@spx.com

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.spx.com.

SPX Corporation reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.

## CUP-04-CEP-USA-02

COPYRIGHT © 2012 SPX Corporation