

MPL

Manual Poultry Loader



innovative · reliable · leading

poly-clip[®]
SYSTEM

- Hocking and bagging of poultry
- Quick and smooth operation
- Individually adjustable to poultry size
- Processes bags from a wicket or strapped bags/ shrink bags

Applications

In combination with single-clip machines of the Easy Clip Line®, the MPL Manual Poultry Loader (bagger) is ideal for efficient packaging of chicken, ducks, geese and poultry parts in bags.

Advantages

- Hygienic stainless steel design for easy cleaning, control splash-proof
- Extremely simple operation due to automatic inflation of the bag
- Suitable for polyethylene, vacuum and shrink bags
- Pressure reducer with filter
- Low air consumption
- Separate air supply – blow air and control air hoses with colour coding
- Simple maintenance
- Can be combined with the VAC vacuum system

Optional equipment

- Base frame
- Horns available in various sizes depending on bag

MPL standard version for bags from a wicket



- Mounting rack right and left (hocking station) for assembly of up to two single-clip machines of the Easy Clip Line® for increased productivity
- Waste bag holder for bag tails
- Pneumatic feeder for strapped bags

Function and operation

The MPL Manual Poultry Loader (bagger) is pneumatically operated and designed for efficient packaging of poultry. The MPL automatically inflates the bags, and the horns move into the bag to keep it open. The poultry is manually pushed through the open horns into the bag to the point where the bag is pulled off. The horns are then retracted to take up the next bag. The filled bag is safely closed with a single-clip machine and, where appropriate, placed in an outer packaging. This ensures fast and simple packaging of the products. When designing the MPL, particular emphasis was placed on strict observance of hygiene requirements and on maximum flexibility for efficient packaging of a wide variety of product sizes. Different horns allow ad-

MPL with pneumatic feeder for strapped bags for even more efficient production



MPL with base frame and EZ 4500 single-clippers as right- and left-hand version

justment to the product weight; if desired, it can also process strapped bags/shrink bags.

Technical data*

Width:	405 mm
Depth:	675 mm
Height:**	300 mm
Weight:	46 kg
Compressed air:	5-6 bar/0.5-0.6 MPa
Air consumption: ca.	10 NL/cycle

* MPL without base frame

** without horns = working height