Vent-Lock™ Safety Cam and Groove Couplings

Application:
- transfer of fluids and solids, with a safer disconnection

Features:
- safety release cam and groove couplings permit the release of static pressure when disconnecting hose assemblies
- venting system protects operator from being sprayed with hazardous or non-hazardous fluids or solids
- rated to **250 PSI**, recommendation based on the use of mating Dixon™ L-style fittings at ambient temperature (**70°F**) with standard Buna-N seal installed, for use at elevated temperature or other unusual operating conditions, consult Dixon™
- does not interchange with standard cam and groove products use only with Dixon™ L-style fittings
- safety orange powder coated cam arms

Materials:
- 316 stainless steel
- consult Dixon™ for availability of other materials

Attachment:
- ferrules, sleeves, bands, and other reliable options

Vent-Lock™ Type A Adapters

female NPT x male adapter

	Size	*316 Stainless Steel* Part #	Price/E
NEW	1"	***L100-A-SS***	**$72.95**
NEW	1½"	***L150-A-SS***	**85.80**
	2"	***L200-A-SS***	**94.70**
NEW	3"	***L300-A-SS***	**215.00**

Vent-Lock™ Type C Couplers

female coupler x hose shank

	Size	*316 Stainless Steel* Part #	Price/E
	1"	***L100-C-SS***	**$111.35**
NEW	1½"	***L150-C-SS***	**160.00**
	2"	***L200-C-SS***	**168.60**

- new Vent-Lock™ inventory will feature safety orange powder coated cam arms

Vent-Lock™ Type E Adapters

male adapter x hose shank

	Size	type E *316 Stainless Steel* Part #	Price/E
NEW	1"	***L100-E-SS***	**$75.40**
NEW	1½"	***L150-E-SS***	**99.00**
	2"	***L200-E-SS***	**106.65**
NEW	3"	***L300-E-SS***	**272.75**