

XTRAVAC 860

Vacuum Packaging Machines



Machine Information XTRAVAC 860

Machine Material	All stainless
Machine Style	Double chamber
Amount of Sealbars	4
Sealbar length inch	34"
Sealbar length mm	860 mm
By-Active sealbars	Optional
Hot wire cut off	Optional
Distance between bars inch	28"
Distance between bars mm	720 mm
Vacuum pump (M3/HP)	302/12.5
Gas flush	Optional
Chamber height inch	8" / 10" / 12"
Chamber height mm	200 / 250 / 300 mm
Machine on wheels	Standard
Leveling legs	Standard
Chamber lid movement	Semi or fully automatic
Machine Dim inch	81" X 41" X 41"
Machine Dim mm	2100 X 1050 X 1050 mm
Chamber Dim inch	41" X 34" X 8"
Chamber Dim mm	1040 X 870 X 200 mm
Machine controls	Digital/Programmable
Machine weight kg	835
Machine weight lbs	1837
Electrical connection	220 V 3 ph/60hz, 400 V 3 ph/50hz
Compressed air	80 psi at 1 cfm
Gross weight kg	900
Gross weight lbs	1900
Package Dimension inch	82" x 43" x 50"
Package Dimension mm	2100 x 1090 x 1285 mm

Model 860

Featuring the longest sealbars and automatic lid movement, the economical XtraVac 860 also offers double seam sealing and the height adjustable, solid UHMW filler plates. The unique design of this model allows a single operator to load and unload product from one side of the machine. This model also features, as a standard, storable program controls and a Busch pump.

XTRAVAC
Vacuum Packaging Machines

VC999 Packaging Systems, Kansas City MO
Tel. 800-728-2999, Fax 816-472-1999