

LOW-ENERGY BOTTLE WASHING MACHINE

Technical Data CB 12-0,5-RV-8,2 ng

Performance	bottles/h	8,000
Control range max.	bottles/h	8,400
Control range min.	bottles/h	4,000
Cycle time	sec.	5.4
Running time	min.	13.2
Bottle length up to	mm	282
Bottle diameter up to	mm	71
Bottles per row	pieces	12
Bottles inside the machine	pieces	1,764
Bottle cell carrier	pieces	152
Pre-heating:		
Total residence time	sec.	232.2
Treatment time effective	sec.	124.2
Caustic:		
Total residence time	min.	6.3
Bottles filled with caustic soak	min.	4.3
Cooling down area:		
Total residence time	min.	4.3
Treatment time effective	min.	1.9
Spraying time effective:		
Hot caustic	sec.	7.2
Caustic I	sec.	3.6
Caustic II	sec.	14.4
Warm-water I	sec.	14.4
Warm-water II	sec.	14.4
Cold-water	sec.	14.4
Fresh-water max.	sec.	14.4
Container contents:		
Pre-soaking	m ³	1.0
Caustic I	m ³	2.2
Caustic II	m ³	0.3
Warm-water I	m ³	0.3
Warm-water II	m ³	0.3
Cold-water	m ³	0.3
Water consumption for 0,5 l bottles	m ³ /h	1.6
Heat consumption while heating the caustic from 15°C to 80°C	kJ x 1000	630
Heat consumption while operating, caustic 80°C	kJ/h x 1000	350
Power connected load	kW	15.7
Operating weight	t	12

Consumption specifications refer to fresh-water 8-13°C, wastewater 35-43°C, bottle infeed 28-33°C, room temperature 15°C, bottle temperature at infeed 15°C
Exchange ratio: 1000 kJ \cong 238.8 kcal \cong 0.45 kg low pressure steam \cong 0.278 kWh