

## Advantages of CB 8-1-R-7,2 VdF ng

- Extremely cost-efficient through mass production
  
- Perfect cleaning performance
  - Residual draining of the bottles
  - Optimum utilization of the soaking time through the high caustic temperature of 80°C which is already in the immersion of the bottles in the soaking bath.
  - Caustic circulation in the soaking bath
  - Long residence time of the bottles in the hot caustic zone with 84°C
  - 5 Spraying zones with 14 stationary internal spray tubes with intense action
  - Large-dimensioned sieve belt provides efficient label removal
  
- Low energy consumption
  - Total isolation of the high-temperature zones
  - Two-stage preheating of the bottles prior to immersion in the caustic soaking
  - Small amount of water and caustic, thus minimizing the heating-up loss
  - Heat recovery from the caustic II and the pre-spraying hot water
  - Balance of caustic carryover through automatic dosing of the caustic II
  - Optimized fluid management and ideal chain management lead to a reduction of the electrical terminal value
  - Controlled vapor exhaust
  - Four-stage cooling down of the bottles after the hot caustic spraying
  
- Life Expectancy for decades
  - Compact and complete execution in stainless steel
  - Extra strong sized main conveyor chains
  - Bottle cell carrier made of high strength steel
  - Robust bottle cells
  
- Service Friendliness
  - Easy accessible components
  - Clear mechanical structure
  - Clear and future-proof electric
  - Decentralized control
  - Large viewing window to check the sprayings
  - Easy maintenance of all bearings by easily accessible lubrication points
  - Easy cleaning thanks to smooth outer surfaces