

SAFETY DATA SHEET

in accordance with 1907/2006/EC (REACH, as amended by 453/2010/EC) and 29 CFR 1910.1200

Revision date: 6 August 2015 Initial date of issue: 5 July 2007 SDS No. 418-4

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

635 SXC Synthetic, Extreme Pressure, Corrosion Resistant Grease

1.2. Relevant identified uses of the substance or mixture and uses advised against

Synthetic base oil lubricating grease. Superior multi-purpose grease for heavy loads, high heat and corrosive environments.

Supplier:

1.3. Details of the supplier of the safety data sheet

Company:
A.W. CHESTERTON COMPANY

860 Salem Street

Groveland, MA 01834-1507, USA

Tel.: +1 978-469-6446 Fax: +1 978-469-6785

(Mon. - Fri. 8:30 - 5:00 PM EST) SDS requests: www.chesterton.com

E-mail (SDS questions): ProductMSDSs@chesterton.com

E-mail: customer.service@chesterton.com

1.4. Emergency telephone number

24 hours per day, 7 days per week Call Infotrac: 1-800-535-5053

Outside N. America: +1 352-323-3500 (collect)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS

Eye Irrit. 2, H319 Skin Sens. 1B, H317

2.1.2. Classification according to WHMIS 1988

Not controlled

2.1.3. Australian statement of hazardous nature

Hazardous according to criteria of Safe Work Australia.

2.1.4. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS

Hazard pictograms:

V

Signal word: Warning

Hazard statements: H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Date: 6 August 2015 SDS No. 418-4

Precautionary statements: P280 Wear protective gloves and eye/face protection.

P305/351/338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337/313 If eye irritation persists: Get medical advice/attention. P302/352 IF ON SKIN: Wash with plenty of soap and water.

P333/313 If skin irritation or rash occurs: Get medical advice/attention. P362/364 Take off contaminated clothing and wash it before reuse.

Supplemental information: None

2.3. Other hazards

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hazardous Ingredients¹	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	1-<10	68584-23-6 271-529-4	01-211949 2627-25	Skin Sens. 1B, H317
Sulfonic acids, petroleum, calcium salts	1-<10	61789-86-4 263-093-4	NA	Skin Sens. 1B, H317
Bis(nonylphenyl)amine	1-<10	36878-20-3 253-249-4	NA	Aquatic Chronic 4, H413
Calcium dodecylbenzenesulphonate	1-<3	26264-06-2 247-557-8	NA	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317
Other ingredients:				
Calcium carbonate	10-20	1317-65-3 215-279-6	NA	Not classified**
Baseoil – unspecified*	3-15	64741-88-4 265-090-8	NA	Not classified**

For full text of H-statements: see SECTION 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Remove to fresh air. If not breathing, administer artificial respiration. Contact physician.

Skin contact: Wash skin with soap and water. Contact physician if irritation persists.

Eye contact: Flush eyes for at least 15 minutes with large amounts of water. Contact physician immediately.

Ingestion: Do not induce vomiting. Contact physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause eye irritation. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

High velocity injection under the skin may leave a bloodless puncture wound subject to infection, disfigurement, lack of blood and may require amputation. Immediate treatment by a surgical specialist is recommended.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Carbon Dioxide, dry chemical, foam or water fog

Unsuitable extinguishing media: High volume water jet

5.2. Special hazards arising from the substance or mixture

Dense smoke.

^{*}Contains less than 3 % DMSO extract as measured by IP 346.

^{**}Substance with a workplace exposure limit.

¹ Classified according to: * 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), California Proposition 65

^{* 1272/2008/}EC, REACH

^{*} WHMIS 2015

^{*} Safe Work Australia [NOHSC: 1008 (2004)]

Date: 6 August 2015 SDS No. 418-4

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Flammability Classification: -

HAZCHEM Emergency Action Code: 3

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Utilize exposure controls and personal protection as specified in Section 8. Wash before eating, drinking or smoking. Injection into the body without immediate medical treatment may cause loss of affected part of the body.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry area.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limit values

Ingredients	OSH <i>A</i> ppm	N PEL ¹ mg/m ³	ACGII ppm	HTLV ² mg/m ³	UK V ppm	VEL ³ mg/m ³	AUSTR. ppm	ALIA ES ⁴ mg/m ³
Benzenesulfonic acid, C10-16- alkyl derivs., calcium salts	-	-	-	-	-	-	-	-
Sulfonic acids, petroleum, calcium salts	_	_	_	_	_	_	-	_
Bis(nonylphenyl)amine	_	_	_	_	_	_	_	_
Calcium dodecylbenzenesulphonate	_	_	_	_	_	_	-	_
Calcium carbonate	(total) (resp)	15 5	(inhal) (resp)	10 3	(inhal) (resp)	10 4	-	10
Oil mist, mineral		5		5		_	_	5

¹ United States Occupational Health & Safety Administration permissible exposure limits.

8.2. Exposure controls

8.2.1. Engineering measures

No special requirements. If exposure limits are exceeded, provide adequate ventilation.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed. If exposure limits are exceeded, use an approved organic vapor respirator for

mists.

Protective gloves: Chemical resistant gloves (e.g., rubber, nitrile).

Eye and face protection: Safety goggles or glasses.

 $^{^{\}rm 2}$ American Conference of Governmental Industrial Hygienists threshold limit values.

³ EH40 Workplace exposure limits, Health & Safety Executive

⁴ Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003].

Date: 6 August 2015 SDS No. 418-4

Other: Long sleeves, long pants and good personal hygiene to minimize skin contact.

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state semi-solid Odour mild

Colour green **Odour threshold** not determined

Initial boiling point not applicable Vapour pressure @ 20°C < 0.0008 hPa (0.00 mm Hg)

Melting point 204°C (> 400°F) % Aromatics by weight

% Volatile (by volume)negligiblepHnot applicableFlash point> 180°C (> 356°F)Relative density1.0 kg/lMethodPM Closed CupWeight per volume8.3 lbs/gal.

Viscosity not determined Coefficient (water/oil) < 1 **Autoignition temperature** not determined Vapour density (air=1) > 1 Rate of evaporation (ether=1) **Decomposition temperature** no data available < 1 Upper/lower flammability or not determined Solubility in water insoluble

explosive limits

Flammability (solid, gas) not applicable Oxidising properties not determined

Explosive properties not determined

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Open flames and red hot surfaces.

10.5. Incompatible materials

Strong acids/bases and strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Carbon Monoxide, Carbon Dioxide, Oxides of Sulfur and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Primary route of exposure Skin and eye contact.

under normal use:

Acute toxicity -

Oral:

Substance	Test	Result
Benzenesulfonic acid, C10-16-alkyl derivs calcium salts	LD50, rat, (OECD 401)	> 2000 mg/kg
Sulfonic acids, petroleum, calcium salts	LD50, rat, (OECD 401)	> 5000 mg/kg
Calcium carbonate	LD50, rat	6450 mg/kg
Bis(nonylphenyl)amine	LD50, rat	> 5000 mg/kg

Date: 6 August 2015 SDS No. 418-4

Dermal:

Substance	Test	Result
Benzenesulfonic acid, C10-16-alkyl	LD50, rabbit	> 2000 mg/kg (read-
derivs., calcium salts		across)
Calcium dodecylbenzenesulphonate	LD50, rabbit	> 4199 mg/kg (read-
		across)
Sulfonic acids, petroleum, calcium salts	LD50, rabbit	> 4000 mg/kg

Inhalation: Not classified due to lack of data.

Substance	Test	Result
Benzenesulfonic acid, C10-16-alkyl	LD50, rat, aerosol	> 1.9 mg/l (read-
derivs., calcium salts		across)

Skin corrosion/irritation:

Substance	Test	Result
Benzenesulfonic acid, C10-16-alkyl	Skin irritation, rabbit	Not irritating (read-
derivs., calcium salts		across)
Calcium dodecylbenzenesulphonate	Skin irritation, rabbit	Irritating
Bis(nonylphenyl)amine	Skin irritation, rabbit	Not irritating

Serious eye damage/ irritation:

May cause eye irritation.

Substance	Test	Result
Benzenesulfonic acid, C10-16-alkyl	Eye irritation, rabbit	Irritating (read-
derivs., calcium salts		across)
Calcium dodecylbenzenesulphonate	Eye irritation, rabbit	Severe irritation (read-across)
Sulfonic acids, petroleum, calcium salts	Eye irritation, rabbit (OECD 405)	Irritating
Bis(nonylphenyl)amine	Eye irritation, rabbit	Not irritating

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

Substance	Test	Result
Bis(nonylphenyl)amine	Skin sensitization, guinea	Not sensitizing
	nia	

Germ cell mutagenicity:

Not classified due to lack of data. Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts: based on available data, the classification criteria are not met.

Carcinogenicity:

As per 29 CFR 1910.1200 (Hazard Communication), this product contains no carcinogens as listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the Occupational Safety and Health Administration (OSHA) or Regulation (EC) No 1272/2008.

Reproductive toxicity: Not classified due to lack of data.

Not classified due to lack of data.

STOT-single exposure: Not classified due to lack of data. Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts: based

on available data, the classification criteria are not met.

STOT-repeated exposure: Not classified due to lack of data. Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts: based

on available data, the classification criteria are not met.

Aspiration hazard: Not classified as an aspiration toxicant.

Other information: None known

Date: 6 August 2015 SDS No. 418-4

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Not determined. Calcium dodecylbenzenesulphonate: 96 h LC50 (fish) = 22 mg/l (OECD 203, read-across). Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene: 96 h LC50 (fish) > 71 mg/l (OECD 203). Sulfonic acids, petroleum, calcium salts: 96 h LC50 (fish) > 10000 mg/l. Oil: practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/ErC50 > 100 mg/l.) Bis(nonylphenyl)amine: 96 h LC50 (fish) < 1000 mg/l.

12.2. Persistence and degradability

Oil: not readily biodegradable. Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts: not readily biodegradable (read-across). Calcium dodecylbenzenesulphonate: readily biodegradable. Sulfonic acids, petroleum, calcium salts: not readily biodegradable (8.6%).

12.3. Bioaccumulative potential

Oil: Calcium dodecylbenzenesulphonate: BCF = 104 (fish, 21 days). log Kow 3.9 - 6; has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

12.4. Mobility in soil

Solubility in water: negligible. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Oil: expected to exhibit low mobility in soil.

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Incinerate absorbed material with a properly licensed facility. Check local, state and national/federal regulations and comply with the most stringent requirement. This product is classified as a hazardous waste according to 2008/98/EC.

European List of Wastes code: 13 02 05

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE TDG: NOT APPLICABLE US DOT: NOT APPLICABLE

14.2. UN proper shipping name

ADR/RID/ADN/IMDG/ICAO: NON-HAZARDOUS, NON REGULATED NON-HAZARDOUS, NON REGULATED NON-HAZARDOUS, NON REGULATED NON-HAZARDOUS, NON REGULATED

14.3. Transport hazard class(es)

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE TDG: NOT APPLICABLE US DOT: NOT APPLICABLE

14.4. Packing group

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE TDG: NOT APPLICABLE US DOT: NOT APPLICABLE

14.5. Environmental hazards

NOT APPLICABLE

14.6. Special precautions for user

NOT APPLICABLE

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

NOT APPLICABLE

14.8. Other information

NOT APPLICABLE

Date: 6 August 2015 **SDS No.** 418-4

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU regulations

Authorisations under Title VII: Not applicable

Restrictions under Title VIII: None

Other EU regulations: None 15.1.2. National regulations

US EPA SARA TITLE III

312 Hazards: 313 Chemicals:

Immediate None

Other national regulations: None 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways Abbreviations

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road and acronyms:

> ATE: Acute Toxicity Estimate **BCF**: Bioconcentration Factor

CLP: Classification Labelling Packaging Regulation (1272/2008/EC)

ES: Exposure Standard

GHS: Globally Harmonized System

ICAO: International Civil Aviation Organization IMDG: International Maritime Dangerous Goods LC50: Lethal Concentration to 50 % of a test population

LD50: Lethal Dose to 50% of a test population

LOEL: Lowest Observed Effect Level

N/A: Not Applicable NA: Not Available

NOAEL: No Observed Adverse Effect Level

NOEL: No Observed Effect Level

OECD: Organization for Economic Co-operation and Development

PBT: Persistent, Bioaccumulative and Toxic substance (O)SAR: Quantitative Structure-Activity Relationship

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

STOT RE: Specific Target Organ Toxicity, Repeated Exposure STOT SE: Specific Target Organ Toxicity, Single Exposure TDG: Transportation of Dangerous Goods (Canada) US DOT: United States Department of Transportation vPvB: very Persistent and very Bioaccumulative substance

WEL: Workplace Exposure Limit

WHMIS: Workplace Hazardous Materials Information System

Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Commission de la santé et de la sécurité du travail (CSST) **Key literature references**

Chemical Classification and Information Database (CCID) and sources for data:

European Chemicals Agency (ECHA) - Information on Chemicals

Hazardous Substances Information System (HSIS) National Institute of Technology and Evaluation (NITE)

Swedish Chemicals Agency (KEMI)

U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Date: 6 August 2015 SDS No. 418-4

Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP] / GHS:

Classification	Classification procedure
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1B, H317	Calculation method

Relevant H-statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H318: Causes serious eye damage. H319: Causes serious eye irritation.

H413: May cause long lasting harmful effects to aquatic life.

Hazard pictogram names: Exclamation mark

Changes to the SDS in this revision: Sections 2.1, 2.2, 3,5.1,8.1,11,12.1, 15.1.2,16

Revision date: 6 August 2015 **Further information:** None

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.