

**SAFETY DATA SHEET**

in accordance with 1907/2006/EC (REACH, as amended by 830/2015/EU) and 29 CFR 1910.1200

**Revision date:** 19 February 2016      **Initial date of issue:** 19 February 2016      **SDS No.** 116EUB

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

651 EU Detergent Lubricating Oil (Bulk)

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Petroleum base lubricant.

**1.3. Details of the supplier of the safety data sheet**

**Company:**

A.W. CHESTERTON COMPANY  
860 Salem Street  
Groveland, MA 01834-1507, USA  
Tel. +1 978-469-6446 Fax: +1 978-469-6785  
(Mon. - Fri. 8:30 - 5:00 PM EST)  
SDS requests: www.chesterton.com  
E-mail (SDS questions): ProductMSDSs@chesterton.com  
E-mail: customer.service@chesterton.com  
EU: Chesterton International GmbH, Am Lenzenfleck 23,  
D85737 Ismaning, Germany – Tel. +49-89-996-5460

**Supplier:**

**1.4. Emergency telephone number**

24 hours per day, 7 days per week  
Call Infotrac: 1-800-535-5053  
Outside N. America: +1 352-323-3500 (collect)

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS**

Asp. Tox. 1, H304

**2.1.2. Classification according to WHMIS 1988**

Not controlled

**2.1.3. Australian statement of hazardous nature**

Not classified as hazardous according to criteria of Safe Work Australia.

**2.1.4. Additional information**

None

**2.2. Label elements**

**Labelling according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS**

**Hazard pictograms:**



**Signal word:**

Danger

**Hazard statements:**

H304      May be fatal if swallowed and enters airways.

**Precautionary statements:**

P301/310      IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P331      Do NOT induce vomiting.  
P405      Store locked up.  
P501      Dispose of contents/container to an approved waste disposal plant.

**Supplemental information:**

None

**2.3. Other hazards**

None

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

Hazardous Ingredients <sup>1</sup>	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification
Distillates (petroleum), hydrotreated heavy naphthenic*	70-80	64742-52-5 265-155-0	01-211946 7170-45	Asp. Tox. 1, H304
Polyoxyethylene oleyl ether phosphate	0.1-1	39464-69-2	NA	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

Other ingredients:

Acetic acid, C11-14-isoalkyl esters, C13-rich	5-10	108419-35-8 283-740-9	NA	Not classified
---	------	--------------------------	----	----------------

For full text of H-statements: see SECTION 16.

\*Contains less than 3 % DMSO extract as measured by IP 346.

<sup>1</sup> Classified according to: \* 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), California Proposition 65  
 \* 1272/2008/EC, REACH  
 \* WHMIS 2015  
 \* Safe Work Australia [NOHSC: 1008 (2004)]

**SECTION 4: FIRST AID MEASURES****4.1. Description of first aid measures****Inhalation:** Remove to fresh air. If not breathing, administer artificial respiration. Contact physician.**Skin contact:** Wash skin with soap and water. Contact physician if irritation persists.**Eye contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Ingestion:** Do not induce vomiting. Contact physician immediately.**4.2. Most important symptoms and effects, both acute and delayed**

Aspiration into the lungs may cause chemical pneumonitis or pulmonary oedema. Direct eye contact may cause eye irritation. High vapor concentration can cause eye and respiratory irritation, headache and dizziness. Prolonged or repeated skin contact may defat the skin and cause skin irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

**SECTION 5: FIREFIGHTING MEASURES****5.1. Extinguishing media****Suitable extinguishing media:** Carbon Dioxide, dry chemical or foam**Unsuitable extinguishing media:** High volume water jet**5.2. Special hazards arising from the substance or mixture**

None

**5.3. Advice for firefighters**

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

**Flammability Classification:** –**HAZCHEM Emergency Action Code:** 3 **Z****SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Cordon off spill area. Surfaces can be slippery. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

**6.2. Environmental Precautions**

Keep out of sewers, streams and waterways.

**6.3. Methods and material for containment and cleaning up**

Contain spill to a small area. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

**6.4. Reference to other sections**

Refer to section 13 for disposal advice.

**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for safe handling**

Utilize exposure controls and personal protection as specified in Section 8.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep container closed when not in use. Store in a cool, dry area.

**7.3. Specific end use(s)**

No special precautions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL <sup>1</sup>		ACGIH TLV <sup>2</sup>		UK WEL <sup>3</sup>		AUSTRALIA ES <sup>4</sup>	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Oil mist, mineral	–	5	–	5	–	–	–	5
Polyoxyethylene oleyl ether phosphate	–	–	–	–	–	–	–	–
Oxo-Alcohol Acetic Acid Ester*	–	–	–	–	–	–	–	–

\*Chesterton recommended limit, 8 hr TWA: 50 ppm, 10 mg/m<sup>3</sup>.

<sup>1</sup> United States Occupational Health & Safety Administration permissible exposure limits.

<sup>2</sup> American Conference of Governmental Industrial Hygienists threshold limit values.

<sup>3</sup> EH40 Workplace exposure limits, Health & Safety Executive

<sup>4</sup> Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003].

**8.2. Exposure controls****8.2.1. Engineering measures**

No special requirements. If exposure limits are exceeded, provide adequate ventilation.

**8.2.2. Individual protection measures**

**Respiratory protection:** Not normally needed. If exposure limits are exceeded, use a half or full-face respirator with combined dust/organic vapour filter (EN filter type A/P).

**Protective gloves:** Chemical resistant gloves (e.g. Viton\*, neoprene, nitrile). \*DuPont's registered trademark.

**Eye and face protection:** Safety goggles or glasses.

**Other:** Impervious gloves and clothing as necessary for repetitive, prolonged contact with liquid.

**8.2.3. Environmental exposure controls**

Refer to sections 6 and 12.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	low viscosity liquid	<b>Odour</b>	mild petroleum odor
<b>Colour</b>	amber	<b>Odour threshold</b>	not determined
<b>Initial boiling point</b>	220°C (428°F)	<b>Vapour pressure @ 20°C</b>	not determined
<b>Melting point</b>	not determined	<b>% Aromatics by weight</b>	< 1%
<b>% Volatile (by volume)</b>	9%	<b>pH</b>	not applicable
<b>Flash point</b>	144°C (290°F)	<b>Relative density</b>	0.9 kg/l
<b>Method</b>	PM Closed Cup	<b>Weight per volume</b>	7.5 lbs/gal.
<b>Viscosity</b>	28 cps @ 25°C	<b>Coefficient (water/oil)</b>	< 1
<b>Autoignition temperature</b>	not determined	<b>Vapour density (air=1)</b>	> 1
<b>Decomposition temperature</b>	not determined	<b>Rate of evaporation (ether=1)</b>	< 1
<b>Upper/lower flammability or explosive limits</b>	not determined	<b>Solubility in water</b>	slightly soluble
<b>Flammability (solid, gas)</b>	not applicable	<b>Oxidising properties</b>	not determined
<b>Explosive properties</b>	not determined		

**9.2. Other information**Kinematic viscosity at 40°C: 16.8 mm<sup>2</sup>/s.**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

Refer to sections 10.3 and 10.5.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

No dangerous reactions known under conditions of normal use.

**10.4. Conditions to avoid**

Open flames and red hot surfaces.

**10.5. Incompatible materials**

Caustics, strong oxidizers like liquid Chlorine and concentrated Oxygen.

**10.6. Hazardous decomposition products**

Carbon Monoxide, Carbon Dioxide and other toxic fumes.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects****Primary route of exposure under normal use:** Inhalation, skin and eye contact.**Acute toxicity -****Oral:**

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	LD50, rat	> 5000 mg/kg, estimated
Acetic acid, C11-14-isoalkyl esters, C13-rich	LD50, rat	> 5000 mg/kg

**Dermal:**

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	LD50, rat	> 2000 mg/kg, estimated
Acetic acid, C11-14-isoalkyl esters, C13-rich	LD50, rabbit	> 3160 mg/kg

**Inhalation:**

High vapor concentration can cause eye and respiratory irritation, headache and dizziness.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	LC50, rat, 4 hours	> 5 mg/l, estimated

**Skin corrosion/irritation:** Prolonged or repeated skin contact may defat the skin and cause skin irritation.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	Skin irritation, rabbit	< 0.5 / 8.0, estimated
Acetic acid, C11-14-isoalkyl esters, C13-rich	Skin irritation, rabbit	Slightly irritating

**Serious eye damage/irritation:** Direct eye contact may cause eye irritation.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	Eye irritation, rabbit	< 15 / 110, estimated
Acetic acid, C11-14-isoalkyl esters, C13-rich	Eye irritation	Slightly irritating

**Respiratory or skin sensitisation:** Distillates (petroleum), hydrotreated heavy naphthenic: Skin sensitization is indicated as non-sensitizing based on data from similar products. Acetic acid, C11-14-isoalkyl esters, C13-rich: did not produce any evidence of skin irritation or skin sensitization response in a repeated insult patch test in human volunteers.

**Germ cell mutagenicity:** Distillates (petroleum), hydrotreated heavy naphthenic: this substance is considered non-mutagenic and has a negative potential for tumor development based on results from the Modified Ames Assay, with a Mutagenic Index of less than 1.0. Acetic acid, C11-14-isoalkyl esters, C13-rich: expected to be non-mutagenic based on data from similar materials.

**Carcinogenicity:** As per 29 CFR 1910.1200 (Hazard Communication), this product contains no carcinogens as listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the Occupational Safety and Health Administration (OSHA) or Regulation (EC) No 1272/2008.

**Reproductive toxicity:** Distillates (petroleum), hydrotreated heavy naphthenic: based on available data, the classification criteria are not met. Acetic acid, C11-14-isoalkyl esters, C13-rich, maternal NOAEL, rat: 500 mg/kg/day; developmental NOAEL, rat: 2500 mg/kg/day.

**STOT-single exposure:** Distillates (petroleum), hydrotreated heavy naphthenic: no data available.

**STOT-repeated exposure:** Distillates (petroleum), hydrotreated heavy naphthenic: based on available data, the classification criteria are not met. Acetic acid, C11-14-isoalkyl esters, C13-rich, NOAEL, 90-day oral subchronic study, rat: 500 mg/kg/day.

**Aspiration hazard:** May be fatal if swallowed and enters airways.

**Other information:** None

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

### 12.1. Toxicity

Distillates (petroleum), hydrotreated heavy naphthenic: available data indicate this product is not acutely toxic. Polyoxyethylene oleyl ether phosphate: Harmful to aquatic life with long lasting effects. (algae, based on data from similar materials.)

### 12.2. Persistence and degradability

Distillates (petroleum), hydrotreated heavy naphthenic: 31% biodegradation (OECD 301F, 28 days). Acetic acid, C11-14-isoalkyl esters, C13-rich: expected to biodegrade slowly in soil and water. Polyoxyethylene oleyl ether phosphate: readily biodegradable.

### 12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy naphthenic: not expected to bioaccumulate. Acetic acid, C11-14-isoalkyl esters, C13-rich: expected to bioaccumulate. Polyoxyethylene oleyl ether phosphate: no data available.

### 12.4. Mobility in soil

Low viscosity liquid. Slightly soluble in water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Distillates (petroleum), hydrotreated heavy naphthenic: large volumes may penetrate soil and contaminate groundwater. Acetic acid, C11-14-isoalkyl esters, C13-rich: expected to have high affinity for adsorption to soil and sediments

### 12.5. Results of PBT and vPvB assessment

Not available

**12.6. Other adverse effects**

None known

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods**

Incinerate absorbed material with a properly licensed facility. Free product should be incinerated or may be amenable to fuels blending. Check local, state and national/federal regulations and comply with the most stringent requirement. This product is not classified as a hazardous waste according to 2008/98/EC.

**SECTION 14: TRANSPORT INFORMATION****14.1. UN number**

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE

TDG: NOT APPLICABLE

US DOT: NOT APPLICABLE

**14.2. UN proper shipping name**

ADR/RID/ADN/IMDG/ICAO: NON-HAZARDOUS, NON REGULATED

TDG: NON-HAZARDOUS, NON REGULATED

US DOT: NON-HAZARDOUS, NON REGULATED

**14.3. Transport hazard class(es)**

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE

TDG: NOT APPLICABLE

US DOT: NOT APPLICABLE

**14.4. Packing group**

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE

TDG: NOT APPLICABLE

US DOT: NOT APPLICABLE

**14.5. Environmental hazards**

NOT APPLICABLE

**14.6. Special precautions for user**

NOT APPLICABLE

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

NOT APPLICABLE

**14.8. Other information**

NOT APPLICABLE

**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

Authorisations under Title VII: Not applicable

Restrictions under Title VIII: None

Other EU regulations: None

**15.1.2. National regulations****US EPA SARA TITLE III****312 Hazards:**

Immediate

**313 Chemicals:**

None

**Other national regulations:** None**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**SECTION 16: OTHER INFORMATION**

**Abbreviations and acronyms:** ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE: Acute Toxicity Estimate  
BCF: Bioconcentration Factor  
CLP: Classification Labelling Packaging Regulation (1272/2008/EC)  
ES: Exposure Standard  
GHS: Globally Harmonized System  
ICAO: International Civil Aviation Organization  
IMDG: International Maritime Dangerous Goods  
LC50: Lethal Concentration to 50 % of a test population  
LD50: Lethal Dose to 50% of a test population  
LOEL: Lowest Observed Effect Level  
N/A: Not Applicable  
NA: Not Available  
NOEC: No Observed Effect Concentration  
NOEL: No Observed Effect Level  
OECD: Organization for Economic Co-operation and Development  
PBT: Persistent, Bioaccumulative and Toxic substance  
(Q)SAR: Quantitative Structure-Activity Relationship  
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail  
SDS: Safety Data Sheet  
STEL: Short Term Exposure Limit  
STOT RE: Specific Target Organ Toxicity, Repeated Exposure  
STOT SE: Specific Target Organ Toxicity, Single Exposure  
TDG: Transportation of Dangerous Goods (Canada)  
US DOT: United States Department of Transportation  
vPvB: very Persistent and very Bioaccumulative substance  
WEL: Workplace Exposure Limit  
WHMIS: Workplace Hazardous Materials Information System  
Other abbreviations and acronyms can be looked up at [www.wikipedia.org](http://www.wikipedia.org).

**Key literature references and sources for data:** Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)  
Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)  
Chemical Classification and Information Database (CCID)  
European Chemicals Agency (ECHA) - Information on Chemicals  
Hazardous Substances Information System (HSIS)  
National Institute of Technology and Evaluation (NITE)  
Swedish Chemicals Agency (KEMI)  
U.S. National Library of Medicine Toxicology Data Network (TOXNET)

**Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP] / GHS:**

Classification	Classification procedure
Asp. Tox. 1, H304	On basis of components and test data

**Relevant H-statements:** H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H400: Very toxic to aquatic life.  
H412: Harmful to aquatic life with long lasting effects.

**Hazard pictogram names:** Health hazard

**Changes to the SDS in this revision:** Initial date of issue.

**Revision date:** 19 February 2016

**Further information:** None

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.