

# 652



## PNEUMATIC LUBRICANT & CONDITIONER

### Description

Chesterton® 652 Pneumatic Lubricant & Conditioner is a high performance, low viscosity, lubricating formula designed to creep into the internal workings of air tools, reduce wear and eliminate the noise associated with rough running equipment. It is a cost-effective oil with high detergency that cleans as it protects and dramatically prolongs the life of pneumatic equipment. The low viscosity and surface tension of 652 Pneumatic Lubricant & Conditioner allow the oil to penetrate deep into the valves, pistons and other air tool components to protect against friction and wear.

Many products used for this application are simply low quality penetrating oils and not designed for the single purpose of maximizing the efficiency of air tools. As such, they often oxidize and allow sludge to build up ultimately inhibiting the efficiency of the pneumatic equipment. Chesterton 652 Pneumatic Lubricant & Conditioner avoids this common problem by engineering a product with a high degree of detergency that keeps the tool running clean and conditioned. Chesterton 652 Pneumatic Lubricant & Conditioner lubricates internal parts such as solenoids, pistons and valves for smoother, more efficient operation. Chesterton 652 further improves operational efficiency of air systems by eliminating tramp and trace moisture from air lines, controls and pneumatic components. Chesterton 652 Pneumatic Lubricant and Conditioner scavenges moisture from the air and removes trapped moisture from critical components. Specialized chemical humectants actually absorb over 10% of their weight in water. It also provides excellent corrosion protection of the pneumatic's internal parts against rusting.

### Composition

Chesterton 652 Pneumatic Lubricant & Conditioner is composed of a high quality light naphthanic petroleum-based lubricant with added conditioners and detergents for high performance. The

Typical Physical Properties		
Appearance		Clear, Amber Liquid
ISO VG	(ASTM D 2422, DIN 51 519)	22
Specific Gravity		0,9
Viscosity	(ASTM D 445, DIN 51 561)	
@ 40°C (104°F) cSt (mm <sup>2</sup> /s)		22
@ 100°C (212°F) cSt (mm <sup>2</sup> /s)		4
Four Ball Wear Test	(ASTM D 2266, DIN 51 350)	
40 kg, 1 hr, 75°C, 1200 RPM		
Scar Diameter		0,5 mm
Weld Load		1568 N, 160 kg
Flash Point	(ASTM D 93, DIN 51 755)	127°C (260°F)
Pour Point	(ASTM D 97, DIN 51 755)	-25°C (-13°F)
Operating Temperature		-23°C to 150°C (-10°F to 300°F)
Pin & Vee Block	(ASTM D 3233)	
Failure Load, Max		7367 N, 750 kg
Torque		3,2 N.m
Coefficient of friction		0,06

added conditioners prevent seals and o-rings from drying out. Anti-oxidants reduce the potential for the formation of varnish and sludge that causes costly shutdown and requires extra maintenance costs to clean equipment. These additives extend lubricating life and allow 652 Pneumatic Lubricant & Conditioner to significantly outperform conventional petroleum-based lubricants.

### Applications

This product was specifically formulated to give exceptional lubrication of air tools, cylinders and air line lubricators, as well as air impact wrenches, air hammers, air drills and air grinders. Chesterton 652 Pneumatic Lubricant & Conditioner can be used for in-line lubricators, production air systems and other high speed air driven equipment. When 652 Pneumatic Lubricant & Conditioner is used as a direct replacement for the standard hydraulic oil, reductions of up to 90% in typical pneumatic maintenance costs can be achieved. The decrease in system downtime and reduction in rejected parts can mean dramatic cost savings.

### Features

- Will not cause sludge buildup
- NSF H2 - Registration number 133944
- Cleans rust, sludge and dirt from all air tools as it lubricates
- Makes tools easier to use and more energy efficient
- Conditioners prevent seals and o-rings from drying out

### Benefits

- Reduce costly maintenance
- Save the cost of replacement parts
- Save costly downtime to manually clean out sludge buildup
- Significantly reduce power consumption
- Prolong life of air tools

### Safety

Before using this product, review the Material Safety Data Sheet (MSDS) or the appropriate safety sheet in your area.

Technical Data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W.CHESTERTON COMPANY DISCLAIMS ALL WARRANTIES EXPRESSED, OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE OR USE. LIABILITY, IF ANY, IS LIMITED TO PRODUCT REPLACEMENT ONLY.



860 Salem Street  
Groveland, Massachusetts 01834 USA  
Tel: (781) 438-7000 • FAX: (978) 469-6528  
[www.chesterton.com](http://www.chesterton.com)

© 2014 A.W. Chesterton Company.  
® Registered trademark owned and licensed by  
A.W. Chesterton Company in USA and other countries.

DISTRIBUTED BY:

FORM NO. 074428

REV. 12/14