

# Lubri-Cup™ OL500 Oiler

Automatic single or multiple point lubricator dispenses Chesterton oil to critical areas, eliminating over and under lubrication.

## Environmentally Friendly

- Lubri-Cup™ OL500 oiler is refillable with Chesterton fluid lubricants.

## User Friendly

- A compact, sturdy design that is simple to operate and maintain. A large LCD screen allows easy setting and monitoring. The unit can operate at high pressure for cold conditions or viscous fluids.

## Equipment Friendly

- Weight balanced design for ease of installation. Robust designed pump for precise and reliable Lubrication. Used with Chesterton oil, it offers extended equipment life and reliability even under the harshest conditions of load, temperature, water and corrosion.

## Cost Effective

- If required the Lubri-Cup™ OL500 oiler can be used for the automatic lubrication of up to 4 points using a divider block.



*Microprocessor controlled, "pulse" delivery system*

*Programmable - Operates up to 24 months*

*Replaceable battery pack or external power supply*

*Lubricates up to 4 points up to 6 m (19 feet) away*

*Sealed microprocessor, rugged metal pump and fittings.*

### Specifications

Fitting	Break-free 3/8" brass
Operating temperature	-15 to 60 °C (5°F~140°F) <i>Lithium ion battery available for temperatures down to -40°C (-40°F)</i>
Typical Pressure	20bar (280psi)
Maximum Pressure	80bar (1,160psi)
Voltage	DC 4.5V (replaceable battery pack)
Oil Volume	500CC

### Order Numbers

Lubri-Cup 500 cc oiler	084319
Lubricup 500 cc oiler with DC Power supply	084464
Lubricup 500 cc oiler with AC Power supply	084457