

**SAFETY DATA SHEET**

in accordance with 1907/2006/EC (REACH, as amended by 830/2015/EC) and 29 CFR 1910.1200

**Revision date:** 5 October 2015

**Initial date of issue:** 5 July 2007

**SDS No.** 167-25

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

706 Rustsolvo®

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Petroleum base cleaner. Penetrating oil - frees nuts, bolts, fittings without injury to base metal.

**1.3. Details of the supplier of the safety data sheet**

**Company:**

A.W. CHESTERTON COMPANY  
860 Salem Street  
Groveland, MA 01834-1507, USA  
Tel.: +1 978-469-6446 Fax: +1 978-469-6785  
(Mon. - Fri. 8:30 - 5:00 PM EST)  
SDS requests: www.chesterton.com  
E-mail (SDS questions): ProductMSDSs@chesterton.com  
E-mail: customer.service@chesterton.com

**Supplier:**

**1.4. Emergency telephone number**

24 hours per day, 7 days per week  
Call Infotrac: 1-800-535-5053  
Outside N. America: +1 352-323-3500 (collect)

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS**

Flam. Liq. 3, H226  
Asp. Tox. 1, H304  
Skin Irrit. 2, H315  
STOT SE 3, H336  
Aquatic Chronic 2, H411

**2.1.2. Classification according to WHMIS 1988**

B3: Combustible liquids

**2.1.3. Australian statement of hazardous nature**

Hazardous according to criteria of Safe Work Australia.

**2.1.4. Additional information**

For full text of H-statements: see SECTIONS 2.2 and 16.

**2.2. Label elements**

**Labelling according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS**

**Hazard pictograms:**



**Signal word:**

Danger

**Hazard statements:**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements:** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261C Avoid breathing vapours/spray.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves.  
 P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P331 Do NOT induce vomiting.  
 P403/233 Store in a well-ventilated place. Keep container tightly closed.

**Supplemental information:** None

### 2.3. Other hazards

None known

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Hazardous Ingredients <sup>1</sup>	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification
Distillates (petroleum), hydrotreated light	40-50	64742-47-8 265-149-8	NA	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic, 2, H411
Distillates (petroleum), hydrotreated heavy naphthenic**	50-55	64742-52-5 265-155-0	01-211946 7170-45	Asp. Tox. 1, H304

For full text of H-statements: see SECTION 16.

\*\*Contains less than 3 % DMSO extract as measured by IP 346.

<sup>1</sup> Classified according to: \* 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), California Proposition 65  
 \* 1272/2008/EC, REACH  
 \* WHMIS 2015  
 \* Safe Work Australia [NOHSC: 1008 (2004)]

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

**Inhalation:** Remove to fresh air. If not breathing, administer artificial respiration. Contact physician immediately.

**Skin contact:** Wash skin with soap and water. Contact physician if irritation persists.

**Eye contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Ingestion:** Do not induce vomiting. Contact physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways. High vapor concentrations cause eye and respiratory tract irritation and dizziness, headache and other central nervous system effects. Prolonged or repeated skin contact may defat the skin and cause skin irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable extinguishing media:** Carbon Dioxide, dry chemical, foam or water spray

**Unsuitable extinguishing media:** High volume water jet

### 5.2. Special hazards arising from the substance or mixture

None

### 5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Flammability Classification: –

HAZCHEM Emergency Action Code: 2 **Z****SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

**6.2. Environmental Precautions**

Keep out of sewers, streams and waterways.

**6.3. Methods and material for containment and cleaning up**

Contain spill to a small area. Keep away from sources of ignition - No smoking. If removal of ignition sources is not possible, then flush material away with water. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

**6.4. Reference to other sections**

Refer to section 13 for disposal advice.

**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for safe handling**

Do not eat, drink or smoke in work area. Keep containers closed when not in use. Ground product transfer. Vapors are heavier than air and will collect in low areas. Utilize exposure controls and personal protection as specified in Section 8.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, dry area.

**7.3. Specific end use(s)**

No special precautions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL <sup>1</sup>		ACGIH TLV <sup>2</sup>		UK WEL <sup>3</sup>		AUSTRALIA ES <sup>4</sup>	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Distillates (petroleum), hydrotreated light	500	–	212*	1200*	–	–	–	–
Oil mist, mineral	–	5	–	5	–	–	–	5

<sup>1</sup> United States Occupational Health & Safety Administration permissible exposure limits.

<sup>2</sup> American Conference of Governmental Industrial Hygienists threshold limit values.

<sup>3</sup> EH40 Workplace exposure limits, Health & Safety Executive

<sup>4</sup> Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003].

**8.2. Exposure controls****8.2.1. Engineering measures**

Use only in well-ventilated areas.

**8.2.2. Individual protection measures**

**Respiratory protection:** Not normally needed. If exposure limits are exceeded, use approved organic vapor respirator (e.g., EN filter type A-P2).

**Protective gloves:** Chemical resistant gloves (e.g. Viton\*, neoprene, nitrile). \*DuPont's registered trademark.

**Eye and face protection:** Safety glasses

**Other:** Impervious clothing (e.g. Viton\*, neoprene or nitrile) as necessary to prevent skin contact. \*DuPont's registered trademark.

**8.2.3. Environmental exposure controls**

Refer to sections 6 and 12.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	thin liquid	<b>Odour</b>	petroleum odor
<b>Colour</b>	blue or green	<b>Odour threshold</b>	not determined
<b>Initial boiling point</b>	not determined	<b>Vapour pressure @ 20°C</b>	not determined
<b>Melting point</b>	not determined	<b>% Aromatics by weight</b>	< 0.5%
<b>% Volatile (by volume)</b>	49.7%	<b>pH</b>	not applicable
<b>Flash point</b>	53.3°C (128°F)	<b>Relative density</b>	0.84 kg/l
<b>Method</b>	PM Closed Cup	<b>Weight per volume</b>	6.99 lbs/gal.
<b>Viscosity</b>	not determined	<b>Coefficient (water/oil)</b>	< 1
<b>Autoignition temperature</b>	not determined	<b>Vapour density (air=1)</b>	> 1
<b>Decomposition temperature</b>	not determined	<b>Rate of evaporation (ether=1)</b>	< 1
<b>Upper/lower flammability or explosive limits</b>	not determined	<b>Solubility in water</b>	negligible
<b>Flammability (solid, gas)</b>	not applicable	<b>Oxidising properties</b>	not determined
<b>Explosive properties</b>	not determined		

**9.2. Other information**

None

**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

Refer to sections 10.3 and 10.5.

**10.2. Chemical stability**

Stable

**10.3. Possibility of hazardous reactions**

No dangerous reactions known under conditions of normal use.

**10.4. Conditions to avoid**

Open flames, heat, sparks and red hot surfaces.

**10.5. Incompatible materials**

Strong oxidizers like liquid Chlorine and concentrated Oxygen.

**10.6. Hazardous decomposition products**

Carbon Monoxide, aldehydes and other toxic fumes.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

**Primary route of exposure under normal use:** Inhalation, skin and eye contact. Personnel with pre-existing dermatitis are generally aggravated by exposure.

**Acute toxicity -****Oral:**

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LD50, rat	> 5000 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic	LD50, rat	> 5000 mg/kg, estimated

**Dermal:**

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LD50, rabbit	> 2000 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic	LD50, rabbit	> 2000 mg/kg, estimated

**Inhalation:**

High vapor concentrations cause eye and respiratory tract irritation and dizziness, headache and other central nervous system effects.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LC50, rat, 4 hours	> 5.28 mg/l
Distillates (petroleum), hydrotreated heavy naphthenic	LC50, rat, 4 hours	> 5 mg/l, estimated

**Skin corrosion/irritation:**

Causes skin irritation.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Skin irritation, rabbit	Not irritating / Slightly irritating / Moderately irritating
Distillates (petroleum), hydrotreated heavy naphthenic	Skin irritation, rabbit	Not irritating

**Serious eye damage/irritation:**

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Eye irritation, rabbit	Not irritating / Slightly irritating
Distillates (petroleum), hydrotreated heavy naphthenic	Eye irritation, rabbit	Not irritating

**Respiratory or skin sensitisation:**

Skin sensitization: based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Skin sensitization, guinea pig	Not sensitizing
Distillates (petroleum), hydrotreated heavy naphthenic	Skin sensitization, guinea pig	Not sensitizing

**Germ cell mutagenicity:**

Based on available data on components, the classification criteria are not met.

**Carcinogenicity:**

As per 29 CFR 1910.1200 (Hazard Communication), this product contains no carcinogens as listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the Occupational Safety and Health Administration (OSHA) or Regulation (EC) No 1272/2008.

**Reproductive toxicity:**

Based on available data on components, the classification criteria are not met.

**STOT-single exposure:**

May cause drowsiness or dizziness.

**STOT-repeated exposure:**

Based on available data on components, the classification criteria are not met.

**Aspiration hazard:**

May be fatal if swallowed and enters airways.

**Other information:**

None

**SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment (based on component data).

**12.2. Persistence and degradability**

Distillates (petroleum), hydrotreated light: can degrade in air, inherently biodegradable. Distillates (petroleum), hydrotreated heavy naphthenic: not readily biodegradable (biodegradation: 31% OECD 301F, 28 days).

**12.3. Bioaccumulative potential**

Distillates (petroleum), hydrotreated heavy naphthenic: not expected to bioaccumulate. Distillates (petroleum), hydrotreated light, Octanol/water partition coefficient (log Kow): 2.1 – 5, estimated.

**12.4. Mobility in soil**

Liquid. Insoluble in water. Floats on water. Distillates (petroleum), hydrotreated heavy naphthenic: large volumes may penetrate soil and contaminate groundwater. Distillates (petroleum), hydrotreated light: will rapidly evaporate to the air if released into the environment. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9).

**12.5. Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6. Other adverse effects**

None known

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods**

Incinerate or fuel blend spent or unused product. Incinerate absorbed material and/or containers with a properly licensed facility. Check local, state and national/federal regulations and comply with the most stringent requirement. This product is classified as a hazardous waste according to 2008/98/EC.

**SECTION 14: TRANSPORT INFORMATION****14.1. UN number**

<b>ADR/RID/ADN/IMDG/ICAO:</b>	UN1993
<b>TDG:</b>	UN1993
<b>US DOT:</b>	UN1993*

**14.2. UN proper shipping name**

<b>ADR/RID/ADN/IMDG/ICAO:</b>	FLAMMABLE LIQUID, N.O.S. (CONTAINS NAPHTHA)
<b>TDG:</b>	FLAMMABLE LIQUID, N.O.S. (CONTAINS NAPHTHA)
<b>US DOT:</b>	FLAMMABLE LIQUID, N.O.S. (CONTAINS NAPHTHA)*

**14.3. Transport hazard class(es)**

<b>ADR/RID/ADN/IMDG/ICAO:</b>	3
<b>TDG:</b>	3
<b>US DOT:</b>	3

**14.4. Packing group**

<b>ADR/RID/ADN/IMDG/ICAO:</b>	III
<b>TDG:</b>	III
<b>US DOT:</b>	III

**14.5. Environmental hazards**

NO ENVIRONMENTAL HAZARDS

**14.6. Special precautions for user**

NO SPECIAL PRECAUTIONS FOR USER

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

NOT APPLICABLE

**14.8. Other information**

**US DOT:** ERG NO.128,  
\*May be reclassified as a combustible liquid and as non hazardous in non-bulk packages  
(maximum capacity of 119 gallons(450 L) or less as a receptacle) (49CFR 173.150 (f),(1),(2))

**IMDG:** EmS. F-E, S-E

**ADR:** Classification code F1 , Tunnel restriction code (D/E)

**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

**Authorisations under Title VII:** Not applicable

**Restrictions under Title VIII:** None

**Other EU regulations:** Directive 96/82/EC on the control of major-accident hazards involving dangerous substances (Petroleum products, qualifying quantities: 2 500 t, 25 000 t).

### 15.1.2. National regulations

#### US EPA SARA TITLE III

<b>312 Hazards:</b>	<b>313 Chemicals:</b>
Immediate	None
Fire	

**Other national regulations:** National implementation of the EC Directive referred to in section 15.1.1.

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION

**Abbreviations and acronyms:** ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE: Acute Toxicity Estimate  
 BCF: Bioconcentration Factor  
 CLP: Classification Labelling Packaging Regulation (1272/2008/EC)  
 ES: Exposure Standard  
 GHS: Globally Harmonized System  
 ICAO: International Civil Aviation Organization  
 IMDG: International Maritime Dangerous Goods  
 LC50: Lethal Concentration to 50 % of a test population  
 LD50: Lethal Dose to 50% of a test population  
 LOEL: Lowest Observed Effect Level  
 N/A: Not Applicable  
 NA: Not Available  
 NOAEL: No Observed Adverse Effect Level  
 NOEL: No Observed Effect Level  
 OECD: Organization for Economic Co-operation and Development  
 PBT: Persistent, Bioaccumulative and Toxic substance  
 (Q)SAR: Quantitative Structure-Activity Relationship  
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)  
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail  
 SDS: Safety Data Sheet  
 STEL: Short Term Exposure Limit  
 STOT RE: Specific Target Organ Toxicity, Repeated Exposure  
 STOT SE: Specific Target Organ Toxicity, Single Exposure  
 TDG: Transportation of Dangerous Goods (Canada)  
 US DOT: United States Department of Transportation  
 vPvB: very Persistent and very Bioaccumulative substance  
 WEL: Workplace Exposure Limit  
 WHMIS: Workplace Hazardous Materials Information System  
 Other abbreviations and acronyms can be looked up at [www.wikipedia.org](http://www.wikipedia.org).

**Key literature references and sources for data:** Commission de la santé et de la sécurité du travail (CSST)  
 Chemical Classification and Information Database (CCID)  
 European Chemicals Agency (ECHA) - Information on Chemicals  
 Hazardous Substances Information System (HSIS)  
 National Institute of Technology and Evaluation (NITE)  
 Swedish Chemicals Agency (KEMI)  
 U.S. National Library of Medicine Toxicology Data Network (TOXNET)

**Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP] / GHS:**

Classification	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Asp. Tox. 1, H304	On basis of components
STOT SE 3, H336	Bridging principle "Dilution"
Skin Irrit. 2, H315	Calculation method
Aquatic Chronic 2, H411	Calculation method

**Relevant H-statements:** H226: Flammable liquid and vapour.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H336: May cause drowsiness or dizziness.  
H411: Toxic to aquatic life with long lasting effects.

**Hazard pictogram names:** Flame, health hazard, exclamation mark, environment

**Changes to the SDS in this revision:** Sections 2.1, 2.2, 3, 4.1, 11, 15.1.2, 16.

**Revision date:** 5 October 2015

**Further information:** None

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.