



SAFETY DATA SHEET

in accordance with 1907/2006/EC (REACH, as amended by 453/2010/EC) and 29 CFR 1910.1200

Revision date: 30 April 2015

Initial date of issue: 25 January 2008

SDS No. 111A-19

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

752 Cold Galvanizing Compound (Aerosol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Zinc rich primer and coating for iron, steel and their welds.

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY
860 Salem Street
Groveland, MA 01834-1507, USA
Tel.: +1 978-469-6446 Fax: +1 978-469-6785
(Mon. - Fri. 8:30 - 5:00 PM EST)
SDS requests: www.chesterton.com
E-mail (SDS questions): ProductMSDSs@chesterton.com
E-mail: customer.service@chesterton.com

Supplier:

1.4. Emergency telephone number

24 hours per day, 7 days per week
Call Infotrac: 1-800-535-5053
Outside N. America: +1 352-323-3500 (collect)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol 1, H222
Skin Irrit. 2, H315
Eye Irrit. 2, H319
STOT SE 3, H336
STOT RE 2, H373
Aquatic Acute 1, H400
Aquatic Chronic 1, H410

2.1.2. Classification according to Directives 1999/45/EC and 1975/324/EEC

Extremely flammable; F+; R12
Irritant; Xi; R36
R66
R67
Dangerous for the environment; N; R50/53

2.1.3. Classification according to 29 CFR 1910.1200 / WHMIS 2015

Aerosol 1, H222
Skin Irrit. 2, H315
Eye Irrit. 2, H319
STOT SE 3, H336
STOT RE 1, H372
STOT RE 2, H373
Aquatic Acute 1, H400
Aquatic Chronic 1, H410

2.1.4. Classification according to WHMIS 1988

B5: Flammable aerosols; D2A: Very toxic materials causing other effects; D2B: Toxic materials causing other effects; A: Compressed gases

2.1.5. Australian statement of hazardous nature

Hazardous according to criteria of Safe Work Australia.

2.1.6. Additional information

For full text of H-statements and R-phrases: see SECTIONS 2.2 and 16.

2.2. Label elements**2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]****Hazard pictograms:****Signal word:**

Danger

Hazard statements:

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to the central nervous system through prolonged or repeated exposure.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe vapours.
 P280 Wear protective gloves and eye/face protection.
 P314 Get medical advice/attention if you feel unwell.
 P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Supplemental information:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (120°F). Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

2.2.2. Labelling according to 29 CFR 1910.1200 / WHMIS 2015**Hazard pictograms:****Signal word:**

Danger

Hazard statements:

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H372 Causes damage to the central nervous system through prolonged or repeated exposure.
 H373 May cause damage to the liver, kidneys and hearing through prolonged or repeated exposure.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements:

Same as section 2.2.1.

Supplemental information:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (120°F). Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

2.3. Other hazards

Contents under pressure.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures**

Hazardous Ingredients ¹	% Wt.	CAS No./ EC No.	REACH Reg. No.	Classification (CLP/GHS)	Classification (67/548/EEC)
Zinc	40-50	7440-66-6 231-175-3	NA	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 (M-factor: 1)	N; R50/53
Acetone	10-20	67-64-1 200-662-2	01-211947 1330-49	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	F; R11 Xi; R36 R66 R67
Xylene	5-10	1330-20-7 215-535-7	NA	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H332/H312 STOT RE 2, H373I Skin Irrit. 2, H315 STOT SE 3, H335	R10 Xn; R20/21 Xi; R38
Methyl Ethyl Ketone	5-10	78-93-3 201-159-0	01-211945 7290-43	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	F; R11 Xi; R36 R66 R67
Petroleum gas**	5-10	68476-86-8 270-705-8	NA	Press. Gas Flam. Gas 1, H220 Carc. 1B, H350 Muta. 1B, H340	F+; R12
Stoddard solvent*	1-5	8052-41-3 232-489-3	NA	Flam. Liq. 3, H226 STOT RE 1, H372D Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	R10 Xn; R65-48/20 Xi; R38 R67 N; R51/53
Carbon Dioxide	1-5	124-38-9 204-696-9	NA	Press. Gas, H280	Not classified
Ethylbenzene	1-2	100-41-4 202-849-4	NA	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332	F; R11 Xn; R20
n-Butyl Acetate	1-2	123-86-4 204-658-1	NA	Flam. Liq. 3, H226 STOT SE 3, H336	R10-66-67

Indications of danger acc. to 67/548/EEC: F+: Extremely flammable; F: Highly flammable; Xn: Harmful; Xi: Irritant; N: Dangerous for the environment

For full text of H-statements and R-phrases: see SECTION 16.

*Contains less than 0.1 % w/w Benzene. **Contains less than 0.1 % w/w 1,3-Butadiene.

¹ Classified according to: * 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), California Proposition 65
* 1272/2008/EC, 67/548/EEC, 99/45/EC, REACH
* WHMIS 2015
* Safe Work Australia [NOHSC: 1008 (2004)]

SECTION 4: FIRST AID MEASURES**4.1. Description of first aid measures**

Inhalation: Remove to fresh air. If not breathing, administer artificial respiration. Contact physician.

Skin contact: Wash skin with soap and water. Contact physician if irritation persists.

Eye contact: Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.

Ingestion: Do not induce vomiting. Contact physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Direct contact and vapors may cause eye, nose and throat irritation. Inhalation of vapor concentrations in excess of exposure limits may result in dizziness, headache and other central nervous system effects. Prolonged or repeated skin contact may defat the skin and cause skin irritation. May cause damage to the liver, kidneys and hearing through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIRE-FIGHTING MEASURES**5.1. Extinguishing media**

Carbon Dioxide, dry chemical or foam. Do not use water on product.

5.2. Special hazards arising from the substance or mixture

Contact with water liberates extremely flammable gases. Pressurized containers, when heated, are a potential explosive hazard.

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Flammability Classification: NFPA Storage Level III; 16 CFR 1500.3 Extremely flammable aerosol

HAZCHEM Emergency Action Code: 3 **Y**

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

No special requirements.

6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Keep away from sources of ignition - No smoking. If removal of ignition sources is not possible, then flush material away with water. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Use only in well-ventilated areas. Shake well before using. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No Smoking. Vapors are heavier than air and will collect in low areas. Vapor accumulations could flash and/or explode if ignited. After handling, wash before eating, drinking or smoking. Utilize exposure controls and personal protection as specified in Section 8.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (120°F). Do not pierce or burn, even after use.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		UK WEL ³		AUSTRALIA ES ⁴	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Zinc	–	15	–	10	–	–	–	10
Acetone	1000	2400	500	1185	500	1210	500	1185
			STEL: 750	1780	STEL: 1500	3620	STEL: 1000	2375
Xylene	100	435	100	434	50	220	80	350
			STEL: 150	651	STEL: 100	441	STEL: 150	655
Methyl Ethyl Ketone	200	590	200	590	200	600	150	445
			STEL: 300	885	STEL: 300	899	STEL: 300	890
Petroleum gas	1000	–	1000	–	1000	–	1000	–
Stoddard solvent	500	2900	100	525	–	–	–	790
Carbon Dioxide	5000	9000	5000	9000	5000	9150	5000	9000
			STEL: 30000	54000	STEL: 15000	27400	STEL: 30000	54000
Ethylbenzene	100	435	20	–	100	441	100	434
			STEL: 125	552	STEL: 125	543	STEL: 125	543
n-Butyl Acetate	150	710	150	–	150	724	150	200
			STEL: 200	–	STEL: 200	966	STEL: 200	950

¹ United States Occupational Health & Safety Administration permissible exposure limits.

² American Conference of Governmental Industrial Hygienists threshold limit values.

³ EH40 Workplace exposure limits, Health & Safety Executive

⁴ Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003].

8.2. Exposure controls**8.2.1. Engineering measures**

Provide sufficient explosion-proof ventilation to keep the vapor concentrations below the exposure limits.

8.2.2. Individual protection measures

Respiratory protection: If exposure limits are exceeded, use approved organic vapor respirator (e.g., EN filter type A/P).

Protective gloves: Chemical resistant gloves (e.g., natural rubber, neoprene or PVC)

Acetone:

Contact type	Glove material	Layer thickness	Breakthrough time*
Full	butyl rubber	0.7 mm	> 480 min.
Splash	Natural rubber	0.6 mm	> 10 min.

*Determined according to EN374 standard.

Eye and face protection: Recommend safety glasses.

Other: Impervious clothing as necessary for repetitive, prolonged skin contact.

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	liquid	Odour	solvent odor
Colour	gray	Odour threshold	not determined
Initial boiling point	56°C (133°F), product only	Vapour pressure @ 20°C	not determined
Melting point	not applicable	% Aromatics by weight	9.4
% Volatile (by volume)	67%	pH	not applicable
Flash point	-18°C (0°F)	Relative density	1.47 kg/l
Method	PM Closed Cup, product only	Weight per volume	12.24 lbs/gal.
Viscosity	not determined	Coefficient (water/oil)	not determined
Autoignition temperature	not determined	Vapour density (air=1)	> 1
Decomposition temperature	no data available	Rate of evaporation (ether=1)	< 1
Upper/lower flammability or explosive limits	LEL: 1.2; UEL: 9.9	Solubility in water	partially soluble
Flammability (solid, gas)	not applicable	Oxidising properties	not determined
Explosive properties	not determined		

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Open flames, heat, sparks and red hot surfaces.

10.5. Incompatible materials

Strong acids, alkalis and strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Carbon Monoxide, Carbon Dioxide and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Primary route of exposure under normal use: Inhalation, skin and eye contact. Personnel with dermatitis and respiratory problems are generally aggravated by exposure.

Acute effects: Direct contact and vapors may cause eye, nose and throat irritation. Inhalation of vapor concentrations in excess of exposure limits may result in dizziness, headache and other central nervous system effects. ATE-mix dermal, 50403 mg/kg. ATE-mix inhalation, 257 mg/l (vapor).

Substance	Test	Result
Acetone	LC50 inhalation, rat	76 mg/l/4 h
Acetone	LD50 dermal rabbit	20000 mg/kg
Acetone	LD50 oral, rat	5800 mg/kg
Xylene	LC50 inhalation, rat	28 mg/l, 4 h
Xylene	LC50 dermal, rabbit	> 4350 mg/kg
Xylene	LD50, oral, rat	2840 mg/kg
Methyl Ethyl Ketone	LC50 inhalation, rat	20 mg/l/4 h
Methyl Ethyl Ketone	LD50 dermal, rabbit	> 8000 mg/kg
Methyl Ethyl Ketone	LD50 oral, rat	> 2600 mg/kg
Stoddard solvent	LC50 inhalation, rat	> 5,5 mg/l/4 h
Stoddard solvent	LC50 dermal, rabbit	> 3000 mg/kg
Stoddard solvent	LD50, oral, rat	> 5000 mg/kg
Ethylbenzene	LC50 inhalation, rat	17,2 mg/l, 4 h
Ethylbenzene	LC50 dermal, rabbit	15354 mg/kg
Ethylbenzene	LD50, oral, rat	3500 mg/kg
n-Butyl Acetate	LC50 inhalation, rat	> 21 mg/l/4 h
n-Butyl Acetate	LD50 dermal rabbit	> 14100 mg/kg
n-Butyl Acetate	LD50 oral, rat	13100 mg/kg

Chronic effects: Prolonged or repeated skin contact may defat the skin and cause skin irritation. Reports have associated repeated or prolonged occupational overexposure to all solvents with permanent brain and nervous system damage. Lab animals exposed to Xylene vapor showed embryo/fetotoxic, hearing loss and liver and kidney effects.

Carcinogenicity: The International Agency for Research on Cancer (IARC) has designated Ethylbenzene as possibly carcinogenic to humans (group 2B).

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: None known

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Solvents (vapor phase): will degrade in air; biodegradable.

12.3. Bioaccumulative potential

Xylene, Ethylbenzene, Methyl Ethyl Ketone, n-Butyl Acetate, Acetone: low potential for bioaccumulation (BCF < 100). The bioaccumulation of Zinc may be important in aquatic environments.

12.4. Mobility in soil

Liquid. Insoluble in water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Solvents (Xylene, Ethylbenzene, Methyl Ethyl Ketone, Stoddard solvent, n-Butyl Acetate, Acetone): will rapidly evaporate to the air if released into the environment.

12.5. Results of PBT and vPvB assessment

Not available

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product should be disposed of as hazardous waste. Incinerate absorbed material with a properly licensed facility. Incinerate pressurized or sealed containers in an approved facility. Check local, state and national/federal regulations and comply with the most stringent requirement. This product is classified as a hazardous waste according to 2008/98/EC.

European List of Wastes code: 15 01 10

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

ADR/RID/ADN/IMDG/ICAO: UN1950

TDG: UN1950

US DOT: UN1950

14.2. UN proper shipping name

ICAO: Aerosols, Flammable

IMDG: Aerosols

ADR/RID/ADN: Aerosols, flammable

TDG: Aerosols, flammable

US DOT: Aerosols, flammable

14.3. Transport hazard class(es)

ADR/RID/ADN/IMDG/ICAO: 2.1

TDG: 2.1

US DOT: 2.1

14.4. Packing group

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE

TDG: NOT APPLICABLE

US DOT: NOT APPLICABLE

14.5. Environmental hazards

NO ENVIRONMENTAL HAZARDS

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

NOT APPLICABLE

14.8. Other information

US DOT: Shipped as Consumer Commodity ORM-D in packaging having a rated capacity gross weight of 66 lb. or less (49 CFR 173.306(i)). ERG NO. 126

IMDG: EmS. F-D, S-U, Shipped as Limited Quantity

ADR: Classification code 5F, Tunnel restriction code (E), Shipped as Limited Quantity

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU regulations

Authorisations under Title VII: Not applicable

Restrictions under Title VIII: None

Other EU regulations: Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers. Directive 94/33/EC on the protection of young people at work.

15.1.2. National regulations

US EPA SARA TITLE III

312 Hazards:

313 Chemicals:

Fire	Zinc	7440-66-6	40-50%
Immediate	Xylene	1330-20-7	5-10%
Delayed	Methyl Ethyl Ketone	78-93-35-10%	
	Ethylbenzene	100-41-4	1-2%
Pressure Release	TSCA: All chemical components are listed in the TSCA inventory.		

Hazardous Materials Identification System (HMIS)

4 = Severe Hazard
 3 = Serious Hazard
 2 = Moderate Hazard
 1 = Slight Hazard
 0 = Minimal Hazard
 * = See Section 8

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	1
Personal Protection	*

Other national regulations: National implementations of the EC Directives referred to in section 15.1.1.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms:	<p>ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways</p> <p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road</p> <p>ATE: Acute Toxicity Estimate</p> <p>BCF: Bioconcentration Factor</p> <p>CLP: Classification Labelling Packaging Regulation (1272/2008/EC)</p> <p>ES: Exposure Standard</p> <p>GHS: Globally Harmonized System</p> <p>ICAO: International Civil Aviation Organization</p> <p>IMDG: International Maritime Dangerous Goods</p> <p>LC50: Lethal Concentration to 50 % of a test population</p> <p>LD50: Lethal Dose to 50% of a test population</p> <p>LOEL: Lowest Observed Effect Level</p> <p>N/A: Not Applicable</p> <p>NA: Not Available</p> <p>NOAEL: No Observed Adverse Effect Level</p> <p>NOEL: No Observed Effect Level</p> <p>OECD: Organization for Economic Co-operation and Development</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance</p> <p>(Q)SAR: Quantitative Structure-Activity Relationship</p> <p>REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)</p> <p>RID: Regulations concerning the International Carriage of Dangerous Goods by Rail</p> <p>SDS: Safety Data Sheet</p> <p>STEL: Short Term Exposure Limit</p> <p>STOT: Specific Target Organ Toxicity</p> <p>TDG: Transportation of Dangerous Goods (Canada)</p> <p>US DOT: United States Department of Transportation</p> <p>vPvB: very Persistent and very Bioaccumulative substance</p> <p>WEL: Workplace Exposure Limit</p> <p>WHMIS: Workplace Hazardous Materials Information System</p> <p>Other abbreviations and acronyms can be looked up at www.wikipedia.org.</p>
Key literature references and sources for data:	<p>Commission de la santé et de la sécurité du travail (CSST)</p> <p>Chemical Classification and Information Database (CCID)</p> <p>European Chemicals Agency (ECHA) - Information on Chemicals</p> <p>Hazardous Substances Information System (HSIS)</p> <p>National Institute of Technology and Evaluation (NITE)</p> <p>Swedish Chemicals Agency (KEMI)</p> <p>U.S. National Library of Medicine Toxicology Data Network (TOXNET)</p>

Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008:

Classification	Classification procedure
Aerosol 1, H222	On basis of components
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Bridging principle "Dilution"
STOT RE 2, H373	Bridging principle "Dilution"
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

Relevant H-statements: H220: Extremely flammable gas.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H280: Contains gas under pressure; may explode if heated.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H336: May cause drowsiness or dizziness.
H373I: May cause damage to the central nervous system, liver and kidneys through prolonged or repeated exposure.
H335: May cause respiratory irritation.
H350: May cause cancer.
H340: May cause genetic defects.
H372D: Causes damage to the central nervous system through prolonged or repeated exposure.
H373K: May cause damage to the liver, kidneys and hearing through prolonged or repeated exposure.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.

Relevant R-phrases: R10: Flammable.
R11: Highly flammable.
R12: Extremely flammable.
R20: Harmful by inhalation.
R21: Harmful in contact with skin.
R36: Irritating to eyes.
R37: Irritating to respiratory system.
R38: Irritating to skin.
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Hazard pictogram names: Flame, exclamation mark, health hazard, environment

Changes to the SDS in this revision: Sections 2.1, 2.2, 3, 4.2, 5.1, 9.1, 11, 15.1.2, 16.

Further information: None

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.