

Lubri-Cup™ VG

Automatic, variable gas, single point lubricator, dispenses Chesterton grease to critical areas, eliminating over and under greasing.

LCD Control Panel

Easy to read LCD panel on the top, permits fast, accurate understanding of the unit settings and current status

User Friendly

A compact, convenient and sturdy design that is simple to install and operate. The unit can operate at high pressure if required

Variable Dispensing Rate

Easy to adjust the rate of grease that is dispensed depending on the bearing diameter and rpm. The unit can be set to deliver the 250 cc of grease from 1 month to 12 months periods.

Self Contained, Moves with Equipment

The Lubricup VG is totally self contained. It can move together with the equipment to assure a continued, correct grease supply.

Can be Easily Turned Off/On

Unit may be turned off if the equipment is stopped for extended periods such as annual maintenance shutdowns

Approvals for Use in Hazardous Environments

This device conforms to Ex ia IIB T4 for use in hazardous areas.



- *Microprocessor controlled, "pulse" delivery system*
- *Variable timer - Operates up to 12 months*
- *Nitrogen gas operated unit*
- *Disposable unit*
- *Shock, vibration Resistant*
- *Easy to set up and operate*
- *Can be turned off if equipment is stopped*

Specifications

Fitting	3/8" PT resilient plastic NPT & BSPT compatible
Operating temperature	-20 to 60 °C (-4° F~140° F)
Maximum Pressure	4.8bar (70psi)
Actuating Gas	Non-flammable Nitrogen
Grease Volume	250CC

Order Numbers

615 #1	084304
615 #2	084305
630	084306
625	Special
633	Special
635	Special

A.W. Chesterton Company
500 Unicorn Park Drive,
Woburn, MA. 01801-3343 USA
www.chesterton.com

Distributed by: