


BOILER CONNECTIONS		RATINGS & CAPACITIES		LTR	DATE	REVISION	BY	REPRESENTATIVE:	
A.(1) STEAM OUTLET	2 1/2" NPT	DESIGN PRESSURE	15 PSIG STEAM					—	
B.(2) LWCO	1" NPT	GROSS OUTPUT	335 MBH						
C.(1) ALWCO	3/4" NPT	STEAM (FROM & AT 212°F)	258 Lbs/Hr						
D.(1) SAFETY VALVE	1" NPT	HEAT RELEASE: (FURNACE ONLY)	125,755 BTU/CuFt					PROJECT:	
E.(1) BOILER BLOWDOWN	1 1/4" NPT	RATED INPUT	399 MBH					—	
F.( ) PRESSURE TROL		HEATING SURFACE (ASME)	29 SqFt					—	
G.(1) FEEDWATER	2" NPT	FURNACE HEATING SURFACE	7.28 Ft						
H.(4) INSPECTION	1 1/2" NPT	FURNACE VOLUME	2.39 CuFt						
J.(1) SIGHTPORT	2" PIPE	STEAMING VOLUME	1.10 CuFt	<b>NOTES</b> 1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET. 2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET. 3. BOILER DESIGN CODE ASME SECTION <u>IV</u> . 4. BOILER INSULATED & COVERED W/22 GA. STEEL JACKET. 5. ALL DIMENSIONS ARE $\pm 1/2$ " UNLESS OTHERWISE NOTED.					
K.(1) SKIM TAP	3/4" NPT	STEAM RELEASE AREA	1.59 SqFt						
L.(2) SIGHT GLASS	1/2" NPT	WATER CAPACITY:							
M.(1) CLEANOUT	3" NPT	(FULL)	31.5 Gals @ 262 Lbs						
N.( )		(NWL)	25.3 Gals @ 210 Lbs						
P.( )		SHIPPING WEIGHT:	1,100 Lbs						
Q.( )									
R.( )									
S.( )									



CHECKED BY	DATE
DRAWN BY	DATE

TRIAD	BOILER MODEL
SCALE	300-LP
1/20	DRAWING No
	—

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.