


BOILER CONNECTIONS		RATINGS & CAPACITIES		LTR	DATE	REVISION		BY	REPRESENTATIVE:						
A.(1) STEAM OUTLET	3" 300# FLG	RATED INPUT	900 MBH						?						
B.(2) LWCO	1" NPT	GROSS OUTPUT	729 MBH												
C.(1) ALWCO	3/4" NPT	DESIGN PRESSURE	150 PSIG STEAM												
D.(1) SAFETY VALVE	3/4" NPT	STEAM (FROM & AT 212°F)	717 Lbs/Hr												
E.(1) BOILER BLOWDOWN	1" NPT	HEAT RELEASE: (FURNACE ONLY)	165,534 BTU/CuFt												
F.(1) PRESSURE TROL	3/4" NPT	HEATING SURFACE (ASME)	74 SqFt												
G.(1) FEEDWATER	1" NPT	FURNACE HEATING SURFACE	11.74 SqFt												
H.(4) INSPECTION	2" NPT	FURNACE VOLUME	5.44 CuFt												
J.(1) SIGHTPORT	2" PIPE	STEAMING VOLUME	2.33 CuFt	<p style="text-align: center;">NOTES</p> 1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET. 2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET. 3. BOILER DESIGN CODE ASME SECTION I. 4. BOILER INSULATED & COVERED w/22 GA. STEEL JACKET. 5. ALL DIMENSIONS ARE ±1/2" UNLESS OTHERWISE NOTED.						PROJECT:					
K.(1) SURFACE BLOWDOWN	1" NPT	STEAM RELEASE AREA	2.79 SqFt												?
L.(2) SIGHT GLASS	1/2" NPT	WATER CAPACITY:													
M.(1) OVERFLOW	1" NPT	(FULL)	69.5 Gals @ 578 Lbs												
N.()		(NWL)	52.1 Gals @ 434 Lbs												
P.()		SHIPPING WEIGHT:	1,700 Lbs												
Q.()															
R.()															
S.()															



CHECKED BY _____ DATE _____
 DRAWN BY ? DATE _____

TRIAD BOILER MODEL 900-HP
 SCALE 1/24 DRAWING No ?

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.