

TECHNICAL DATA SHEET

Easy Strip the splicing tool

TECHNICAL CHARACTERISTICS

Carrier type	Polyester, transparent (0.050mm)
Adhesive type	modified acrylic adhesive
tape thickness (without liner)	0.220mm
liner, colour	siliconised havanna paper
liner, thickness/weight	0.075mm - 85g/m ²
Abwicklungskraft	10 cN/50mm
Lösewert	40cN/50mm
adhesion to steel	2000cN/20mm
adhesion to PC	2300cN/20mm
adhesion to glass	2300cN/20mm
adhesion to PP	700cN/20mm
Dehnung auf BA-Stahl	1mm/3h

APPLICATION PROCEDURE

Keep the tape in its original packaging until use.

For optimum results, an even rub down pressure must be applied to the taped area to create the best possible adhesion between tape and the substrates.

Remove the liner prior to usage.

The tape should be applied to clean and dry surfaces.

PACKAGING, TRANSPORT AND STORAGE:

During transport and storage the product should always be protected against direct sunlight and extremes in temperature and humidity and contained in its original packaging. Once removed from its packaging, it should be promptly applied and remain shielded from direct sunlight and extreme temperature as well as protected against dust and other impurities.

recommended temperatur 15 to 30°C

recommended relative humidity 40 to 75%

maximum storage periods 12 month

TOLERANCES

width [+/-1.0] x length [+/-0.5]mm

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. Inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice.

last update: Dezember 2013