Series 1300



The **Series 1300** is LSI's line of labelers specifically designed for Top Labeling of boxes, caps, and any other flat top containers. Other typical labeling applications included labeling of DVD/CD cases, food products, cosmetics or clam shell container labeling. The **Series 1300** is designed to work with any of LSI's standard labeling heads such as the Series 30 & 40 Apply Only Labeling Heads and Series 20 Print & Apply Labeling Head. Whether you want to print and applying shipping labels to outbound orders as they travel out your case sealer or if you want to apply a promotional stickers to one your products, this machine is built for easy changeover, accurate label placement, and continuous 24-7 use.

The Series 1300 includes such features as:

- Available as synchronous dispense (Model 010 Wipe on Applicator w/ a brush or with a tamp applicator.
- Rigid mounting of the labeling head(s) for high accuracy labeling
- Head mount assembly is highly adjustable for easy adjustment of vertical label placement.
- Bright LCD digital display, easy to read, simple menus, remote mounting available
- PLC Controls flexible, I/O expansion kit upgrade optional
- Re-settable product and label counters
- 50 Recipe storage locations, for easy set-up and repeatable product change over
- Auto Teach Label Sensing
- Heavy duty aluminum plate and stainless steel construction, designed for 24 x 7 duty
- Available in Right or Left Hand Configurations
- Thermal Transfer or Hot Stamp Date/Lot Coding
- · Remote Display Mounting





Labeling Systems Inc.

32 Spruce Street Oakland, NJ 07436 Tel: (201) 405-0767 Fax: (201) 405-1179

Email: LSI@LabelingSystems.com www.labelingsystems.com



Performance		
Speed	60 PPM	
Accuracy	+/- 1/32	
Product Specifications		
Туре	Boxes (corrugated or	
	chipboard), or any other flat	
	surface such as clam shell	
	containers	
Length	4" min to 36" max	
Width	4" min to 8" max	
Height	4" min to 24" max	
Label Specifications		
Roll Size	12" O.D. on 3" core	
Material	Film or paper	
Conveyor		
Туре	Aluminum plate – delrin chain	
Avail. Lengths	5.5, 8.0', 10.0'	
Widths	3", 4.5", 6", 7.5"	
Heights +/- 2"	28", 32", 36", 40", 44"	
System Frame and Head Mounting		
Туре	Fully integrated aluminum/steel	
	frame, leveling pads std. and	
	castors optional	
Utility Requirements		
Electrical	115v 60 cycle 10 amp	
Air	Some options may require air – 80 PSI, 2 CFM	



Available with Wipe-on with brush or with a Tamp Applicator (Model 010 Wipe-on with brush featured above)




32 Spruce Street Oakland, NJ 07436 Tel: (201) 405-0767

Fax: (201) 405-1179 www.labelingsystems.com Email: LSI@LabelingSystems.com




Model 1300T Print & Apply with optional enclosure

Series 30 Apply Only Stepper motor drive with a 5" wide web capacity. Up to 400"/min dispense speed. PLC controls and self teaching label	
and self teaching label	
sensor are std.	-



Labeling Head Options







Consult factory for any other options or requirements.